

Forstline winches are unique in all details and are available in several sizes.

The winch was developed and constructed in a close relation with the user.

The brake and clutch are easily operated by pulling the nylon lines.

Optimum security for the operator is ensured with several screens offering protection from moving parts.

W-10014-EH can be equipped with hydraulic device for unwinding wire rope.

A special developed"noiseless" chain pulling system ensures a good working environment. of the wire cable.

Optimum distance between top pulley and wire roll ensures a perfect spooling

Several compartments for storing equipment and the possibility of mounting a trailer coupling.







Several protection screens and a "noiseless" chain tightener ensures a safe and good working environment for the user.



The unique design of the winch includes the smallest detail. The sturdy frame construction is made from special steel. A solid, wide blade/butt plate and lower pulley are standard. Chainsaw holder and trailer attachment are optional.



Two integrated storage compartments for accessories, is standard.

Technical data:	W-10014 / W-10014-EH
Pulling power	10 ton
Tractor power	Ca. 60 kW
-3point linkage	Kat. II - III
Weight	825 kg /860 kg
Wire standard ø x m	12 mm x 70 m
Wire max. ø x m	14 mm x 120 m
Pulling speed v/540 rpm	0,4 - 0,9 m/s
PTO attachment height	70 cm
Height top pulley	190 cm
Total height	230 cm
Dozerblade	86 x 200 cm



The PTO driven self-contained W-10014-EH with optional hydraulic system assures optimal performance.

hydraulic device for unwinding wire rope, relieves the hard work, when pulling the wire out.

e constantly develop our machines, we reserve the right to make technical changes!

Importer / Distributor



Manufacturer.

Fransgård Maskinfabrik A/S Fredbjervej 132 9640 Farsø **Denmark** Tlf.+45 98632122 www.fransgard.dk