



KHD 3.4/35 AG

Honda-powered aluminum-series cold water pressure washers. Easily configure from cart to skid to match your cleaning application.

TECHNICAL DATA AND EQUIPMENT



KHD 3.4/35 AG

- Compact, light and very mobileCrankshaft pump

Technical data		
Order no.		9.807-720.0
EAN code		886622017554
Flow rate	I/h / GPM	3.5
Working pressure	PSI	3500
Max. pressure	PSI	3500
Weight	kg	100
Dimensions (L × W × H)		41 × 22 × 24

Equipment Spray gun		
Spray gun		standard
High-pressure hose	ft	50
ANTI!Twist		-
Pressure cut-off		-
Servo Control		-























								T
			May working					
	Order no.	ID	pressure	Length		Price	Description	
1	6.391-342.0	ID 8	315 bar	10 m			To extend the operating radius with the high-pressure clean er. Connection on both sides M22 x 1.5.	A
2	6.390-293.0	ID 8	315 bar	30 m				•
des								
3	6.391-883.0	ID 6	400 bar	10 m			With rotary coupling, 2 x M 22 x 1,5	A
4	6.391-354.0	ID 8	400 bar	10 m			To extend the operating radius with the high-pressure clean er. Connection on both sides M22 x 1.5.	•
5	6.389-709.0	ID 8	400 bar	15 m			With rotary coupling, 2 x M 22 x 1.5	•
6	6.390-294.0	ID 8	400 bar	30 m				•
7	6.390-178.0	ID 8	400 bar	1.5 m				
nectio	ns at both ends	•						
8	6.391-864.0	ID 8	400 bar	10 m			Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant_non-colour-bleeding ma-	A
9	6.391-887.0	ID 8	400 bar	20 m			terial. With rotary coupling, 2 x M 22 x 1,5	A
		'						
10	6.391-875.0	ID 6	300 bar	10 m			With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection, NW 6/155°//200 bar	
							and kink protection. NW 0/133 C/300 but	
11	6.391-882.0	ID 6	400 bar	10 m			With patented AVS connection in the trigger gun (pivot-mounted).	
12	6.391-351.0	ID 8	400 bar	10 m			With patented AVS connection in the trigger gun (rotatable)	. 🗆
13	6.388-886.0	ID 8	400 bar	1.5 m			Connection hose in longlife quality with 2x M22 x 1.5, with angled connection on one side.	
	2 3 4 5 6 7 7 Inecticities 9 10 11 12 13 13	1 6.391-342.0 2 6.390-293.0 des 3 6.391-883.0 4 6.391-354.0 5 6.389-709.0 7 6.390-178.0 nections at both ends 8 6.391-864.0 9 6.391-887.0 10 6.391-875.0 11 6.391-882.0	1 6.391-342.0 ID 8 2 6.390-293.0 ID 8 3 6.391-883.0 ID 6 4 6.391-354.0 ID 8 5 6.389-709.0 ID 8 6 6.390-294.0 ID 8 7 6.390-178.0 ID 8 8 6.391-864.0 ID 8 9 6.391-887.0 ID 8 10 6.391-875.0 ID 6 11 6.391-882.0 ID 6 12 6.391-351.0 ID 8 13 6.388-886.0 ID 8	1 6.391-342.0 ID 8 315 bar 2 6.390-293.0 ID 8 315 bar des 3 6.391-883.0 ID 6 400 bar 4 6.391-354.0 ID 8 400 bar 5 6.389-709.0 ID 8 400 bar 6 6.390-294.0 ID 8 400 bar 7 6.390-178.0 ID 8 400 bar nections at both ends 8 6.391-864.0 ID 8 400 bar 10 6.391-875.0 ID 6 300 bar 11 6.391-875.0 ID 6 400 bar 12 6.391-351.0 ID 8 400 bar	Order no. ID pressure Length 1 6.391-342.0 ID 8 315 bar 10 m 2 6.390-293.0 ID 8 315 bar 30 m des 3 6.391-883.0 ID 6 400 bar 10 m 4 6.391-354.0 ID 8 400 bar 10 m 5 6.389-709.0 ID 8 400 bar 15 m 6 6.390-294.0 ID 8 400 bar 1.5 m 7 6.390-178.0 ID 8 400 bar 1.5 m nections at both ends 8 6.391-864.0 ID 8 400 bar 10 m 9 6.391-864.0 ID 8 400 bar 10 m 10 6.391-875.0 ID 6 300 bar 10 m 11 6.391-875.0 ID 6 400 bar 10 m 12 6.391-351.0 ID 8 400 bar 10 m 13 6.388-886.0 ID 8 400 bar 1.5 m	Order no. ID pressure Length 1 6.391-342.0 ID 8 315 bar 10 m 2 6.390-293.0 ID 8 315 bar 30 m des 3 6.391-883.0 ID 6 400 bar 10 m 4 6.391-354.0 ID 8 400 bar 10 m 5 6.389-709.0 ID 8 400 bar 15 m 6 6.390-294.0 ID 8 400 bar 30 m 7 6.390-178.0 ID 8 400 bar 1.5 m nections at both ends 8 6.391-864.0 ID 8 400 bar 10 m 9 6.391-875.0 ID 8 400 bar 10 m 10 6.391-875.0 ID 6 300 bar 10 m 11 6.391-875.0 ID 8 400 bar 10 m 12 6.391-351.0 ID 8 400 bar 10 m 13 6.388-886.0 ID 8 400 bar 1.5 m	Order no. ID pressure Length Price 1 6.391-342.0 ID 8 315 bar 10 m 2 6.390-293.0 ID 8 315 bar 30 m des 3 6.391-883.0 ID 6 400 bar 10 m 4 6.391-354.0 ID 8 400 bar 10 m 5 6.389-709.0 ID 8 400 bar 15 m 6 6.390-294.0 ID 8 400 bar 1.5 m 7 6.390-178.0 ID 8 400 bar 1.5 m nections at both ends 8 6.391-864.0 ID 8 400 bar 10 m 9 6.391-887.0 ID 8 400 bar 10 m 10 6.391-875.0 ID 6 300 bar 10 m 11 6.391-351.0 ID 8 400 bar 10 m 12 6.391-351.0 ID 8 400 bar 10 m 13 6.388-886.0 ID 8 400 bar 1.5 m	Order no. ID pressure Length Price Description 1 6.391-342.0 ID 8 315 bar 10 m To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 x 1.5. 2 6.390-293.0 ID 8 315 bar 30 m With rotary coupling, 2 x M 22 x 1.5. 3 6.391-883.0 ID 6 400 bar 10 m With rotary coupling, 2 x M 22 x 1.5. 4 6.391-884.0 ID 8 400 bar 15 m To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 x 1.5. 5 6.389-709.0 ID 8 400 bar 15 m With rotary coupling, 2 x M 22 x 1.5 6 6.390-294.0 ID 8 400 bar 30 m 1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5). nections at both ends 8 6.391-864.0 ID 8 400 bar 10 m Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1.5 with anti-kink protection. NW 6/155°C/300 bar 10 6.391-875.0 ID 6 3

[☐] Available accessories. ▲ Extension hose.









		Order no.	Flow rate		Price	Description
Trigger guns	· ·			'		
High-end HP trigger gun	1	4.775-823.0				High-end spray guns with optimised flow. Small pressure losses also with water volumes up to 2500 l/h. Robustness and durability for professional use. Food-safe and saltwater-resistant materials offer the best conditions for use in the food sector and in industry. Connector for HP hoses M 22 × 1.5.
Quick connect						
Quick coupling	2	6.401-458.0				For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray Lance interface. With M 22 x 1.5 internal thread.
Male coupling	3	6.401-459.0				Hardened stainless steel male coupling for quick coupling 6.401-458. With M 22 x 1.5 external thread.

[☐] Available accessories. ▲ Extension hose.







		Order no.	Max. working pressure	Length		Price	Description
Spray lance 250 mm lance, non-rotatable	1	4.760-667.0		250 mm			250 mm stainless steel lance. With manual coupling. Non-ro-tatable.
Gutter cleaner Gutter cleaning lance	2	2.642-305.0					The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.

[☐] Available accessories. ▲ Extension hose.





		Г	Г			
		Order no.	Nozzle size		Price	Description
Power nozzle spray angle 25°						
25° power nozzle for cleaning agent suction	1	2.884-521.0	250			Brass power nozzle for low pressure operation and cleaning agent suction.

[☐] Available accessories. ▲ Extension hose.





		Order no.			Price	Description
Adapters						
Sealing cone complete	1	4.424-004.0				In order to install high-pressure hose with male coupling on thread with M22 x 1.5 Alternative:4.111-032.0 Adapter 4 - Device new / Hose old Swivel

[☐] Available accessories. ▲ Extension hose.





		Order no.	Flow rate		Price	Description
Push-on washing brush						
Push-on wash brush	1	4.762-497.0				The wash brush is fitted directly onto the devices' new dual and triple nozzles using clamping.

[☐] Available accessories. ▲ Extension hose.