

RUNNING GEAR AND CHASSIS




H&S HAS A MODEL TO FIT YOUR OPERATION


Superior Construction and Performance on ALL MODE

MODEL 612 12 TON

 The tele-pole is made of structural tubing and the mounting plates have wide spacing between them to reduce sway and increase the strength of the pole.

 Front and rear stake pockets. wear pockets are standard on ALL MODELS!












• H&S models 410, 412, 415, 612, 614, and 61 front spindles with structural bracing to withstar from shock loads. The H&S heavy running gears through 622 – utilize thrust bearings to assure smooth turning and straight trailing.





• The H&S m and use tru the use of v

NNING GEAR FEATURES


ALL WEAR PROTECTIO

King Pin, Hitch Pin, Spindles, Tie Rod Ends and Tie Rod Steering Pivot Poir all wear protected by replaceable oil impregnated steel bushings and are grease





G SECTION REACH FEATURES:



- No rotating collars or moving parts to wear out.
- The Square C-Section Reach provides both strength and flexibility.
- Torsional flexibility without rotating collars.

MODEL - Running Gears	410 Single Axle	412 Single Axle	415 Single Axle	417 Single Axle
CAPACITY	10 TON	12 TON	15 TON	17 TON
WEIGHT W/TIRES	1126# W/12.5L	1190# W/12.5L	1520# W/16.5L	2100# W/19L
TREAD WIDTH	80"	80"	80"	87"
SPINDLES	2"	21/4"	23/4"	3"
HUBS	6 BOLT	8 BOLT	8 BOLT	10 BOLT
BOLSTER	3" X 8"	3" X 8"	4" X 8"	4" X 8"
C-REACH	7 GAUGE	7 GAUGE	3%" WELDMENT	3%" WELDMENT
WHEEL BASE	119" TO 159" IN 10" INCREMENTS		119" TO 179" IN 10" INCREMENTS	
STANDARD WHEEL	15 X 10	15 X 10	16.1 X 14	16.1 X 16
WHEEL OPTIONS	N/A	16.1 X 11, 22.5 X 8 22.5 X 13.5	22.5 X 8, 22.5 X 13.5	16.1 X 11, 22.5 X 8 22.5 X 13.5
BRAKES	N/A	OPT. HYD. SURGE		
BACK HITCH	YES	YES	YES	YES
TELESCOPING POLE	77" FIXED, EXTENDS TO 89"		FIXED AT 89"	

MODEL - Running Gears	Tandem Axle	Tandem Axle	Tandem Axle	Tandem Axle
CAPACITY	12 TON	14 TON	17 TON	22 TON
WEIGHT W/TIRES	1524# W/12.5L	1620# W/12.5L	2480# W/16.5L	3580# W/21.5L
TREAD WIDTH	80"	80"	80"	87"
SPINDLES	2"	21/4"	23/4"	3"
HUBS	6 BOLT	8 BOLT	8 BOLT	8 BOLT
BOLSTER	3" X 8"	4" X 8"	4" X 8"	4" X 8"
C-REACH	7 GAUGE	7 GAUGE	3/8" WELDMENT	¾" WELDMENT
WHEEL BASE	119" TO 159" IN 10" INCREMENTS		119" TO 179" IN 10" INCREMENTS	
STANDARD WHEEL	15 X 10	15 X 10	16.1 X 14	16.1 X 18 OR 22.5 X 13.5
WHEEL OPTIONS	N/A	16.1 X 11	N/A	N/A
BRAKES	N/A	OPT. HYD. SURGE	OPT. HYD. SURGE	OPT. HYD. SURGE
BACK HITCH	N/A	N/A	N/A	N/A
TELESCOPING POLE	77" FIXED, EXTENDS TO 89"		FIXED AT 951/2"	FIXED AT 89"

CHASSIS





ASAE Stress Tested

 H&S 24/26 Chassis can accommodate 22', 24' & 26' front and rear unload industrial forage boxes and the Big Dog forage boxes, 22', 24' & 26' Wide Body forage boxes.

MODEL - Chassis	4124 Chassis	24/26 Chassis		
CAPACITY	44,000#	48,000#		
APPROXIMATE WEIGHT W/TIRES	4,500#	7,150#		
TIRE CHOICES	425 X 22.5 -TRUCK TIRES 21.5L X 16.1 - 18 PLY FLOTATION TIRES 550/45 X 22.5 - 16 PLY FLOTATION TIRES	425 X 22.5 - TRUCK TIRES 550/45 X 22.5 - 16 PLY FLOTATION TIRES 600/50 X 22.5 - 16 PLY FLOTATION TIRES		
TREAD WIDTH	90"	100"		
SPINDLES	3" STRESS PROOF	3" STRESS PROOF		
HUBS	10 BOLT	10 BOLT-12,000#		
OVERALL LENGTH	29' 5"	31' 4"		
SCALE	OPTIONAL	OPTIONAL		
BRAKES	OPTIONAL ELECTRICALLY ACTIVATED OVER HYDRAULIC BRAKE SYSTEM W/CAB CONTROL BOX			
JACK	STANDARD	STANDARD		



STRONG HERITAGE STRONG PEOPLE STRONGER FUTURE!

For over 50 years, H&S Manufacturing has made life better. Our team is committed to building long-lasting relationships and high performance machinery. As we continue to grow and move forward we want you to farm smarter with our most reliable and innovative farming equipment.

H&S is proud to be American Made!

Warranty: See operators manual for warranty details and limitations. H&S reserves the right to change its products or the description at any time without notice or obligation.









Models and specifications are subject to change without prior notice.

10/18 3M

H&S MANUFACTURING

2608 S. Hume Avenue
Telephone (715) 387-3414

FAX (715) 384-5463 • Website www.hsmfgco.com
MARSHFIELD, WI 54449

