

	Front Unload	RTX620	RTX622	RTX624	RTX626
	Front & Rear Unload	RTX220	RTX222	RTX224	RTX226
<b>DIMENSIONS</b>					
Floor Length		20'6"	22'6"	24'6"	26'6"
Overall Length	RT/RTX600	23'8"	25'8"	27'8"	29'8"
	RT/RTX200	24'7"	26'7"	28'7"	30'7"
Inside Height (without roof)	std height				
	high sides	7'3"	7'3"	7'3"	7'3"
Overall Height (without roof)	top of side				
	std height				
	high sides	106"	106"	106"	106"
	top of door pivot (RT/RTX200 only)				
	std height				
	high sides	115"	115"	115"	115"
Less 4" truck & trailer mounts (except on XT1600 trailer*)					
Overall Height (with roof) - wagon mount version	std height				
	high sides	126.5"	126.5"	126.5"	126.5"
Inside Width		89.5"	89.5"	89.5"	89.5"
Overall Width with conveyor extension up		109.5"	109.5"	109.5"	109.5"
Stringer Width/Height					
	truck/XT2200 trailer mount	33.5"/6"	33.5"/6"	33.5"/6"	33.5"/6"
	wagon mount	42"/10"	42"/10"	42"/10"	42"/10"
Capacity (struck level) cu. ft. (without roof)	(6'3") std height				
	(7'3") high sides	1108	1217	1325	1433
Capacity cu. ft. (with roof)	(6'3") std height				
	(7'3") high sides	1326	1456	1585	1714
<b>SPECIFICATIONS</b>					
Front Apron Drive Shaft		2"	2"	2"	2"
Rear Drive Shaft (RT/RTX200)		2"	2"	2"	2"
Tubular Upright Spacing		16"	16"	16"	16"
All Steel Frame - 24" centers (no wood)		Std 16"	Std 16"	Std 16"	Std 16"
HD Tubular Floor Supports		2x2	2x2	2x2	2x2
HD Top Rail Formed (no side supports needed)		Std	Std	Std	Std
Commercial Grade Geardrive (no worm gears)		Std	Std	Std	Std
<b>STANDARD FEATURES</b>					
RT Variable Speed System - 0-17"/minute (PTO drive standard)		Std	Std	Std	Std
Apron Chains (heavy duty pintle)		667X	667X	667X	667X
Spring Loaded/Torsion Style Apron Tightener (RT/RTX200)		Std 220	Std 222	Std 224	Std 226
Direction Control System (patented)					
	Front to Rear Selection with No Coupler Change	Std 220	Std 222	Std 224	Std 226
Auger Feathering System & Conveyor Clutch/Safety Clutch		Std	Std	Std	Std
Cross Conveyor Chain Hold-Downs		Std	Std	Std	Std
Fold-Down Conveyor Extension with Lift Assist		Std	Std	Std	Std
Superslide, Solid Poly Floor (no plywood) (RT/RTX200, RTX600)		Std	Std	Std	Std
12" Higher Sides with 4th Beater System		Std	Std	Std	Std
Rear Gate Delay System (RTX200)		Std 220	Std 222	Std 224	Std 226
<b>OPTIONAL EQUIPMENT</b>					
Hydraulic Front Drive System (in lieu of PTO)		Opt	Opt	Opt	Opt
Hydraulic In-Cab Controls (in lieu of PTO) - includes hyd lift conveyor		Opt	Opt	Opt	Opt
36" Fold-Down Cross Conveyor Extension (in lieu of standard 24")		Opt	Opt	Opt	Opt
Hydraulic Lift Option for Fold-Down Cross Conveyor Extension		Opt	Opt	Opt	Opt
Roof Assembly (removable)		Opt	Opt	Opt	Opt
Roof Hood Assembly (right hand, open top units only)		Opt	Opt	Opt	Opt
Rear Grain Kit (RT/RTX200 only)		Opt 220	Opt 222	Opt 224	Opt 226
	False Front Gate for Grain Kit	Opt	Opt	Opt	Opt
Truck Mount/Trailer Mount/Wagon Mount		Opt	Opt	Opt	Opt
Tarp Systems (with front enclosures)					
	Front to Back Scissor Tarp (electric)	Opt	Opt	Opt	Opt
	Side to Side Roll Tarp (electric)	Opt	Opt	Opt	Opt
Clad Tuff Fiberglass Sides & Back		Opt	Opt	Opt	Opt
Barn Door Rear Gate with Closure (RTX200 only)		Opt 220	Opt 222	Opt 224	Opt 226