

Model	Style	Suspension	(Trailer & Load)	Tread Width	Axle Configuration	Heavy Duty Hubs	(Depends on Tires)	Frame Design	Bed Width	Stake Spacing	Bed Height	Overall Width w/600/50x22.5	Overall Length	Bed Length	Hitch and Hitch Supports	Clevis Hitch	Articulating Ag. Hitch	Weight- Approx.	Options	Tires	Brakes	Safety Chair
XTS22-216+	Tandem w/ suspension	Leaf Spring	48,000#	83" w/600/50x22.5	Tandem - non steer 25,000# x 2 - High Speed	10 Bolt - Oil bath	40 mph	4x8 Tubular	42"	33.5" std / 42" Opt	44" w/600/50x22.5	106.5"	25' 5.5"	18'	Extra Heavy Duty	Standard	Optional	5,540# w/600/50x22.5		600/50x22.5 High Float 425/65X22.5 w/Alum. 11Rx22.5 Dual Wheels	Hydraulic Manual Hydraulic Foot Pedal Air	Optional
XTS22-240+	Tandem w/ suspension	Leaf Spring	48,000#	83" w/600/50x22.5	Tandem - non steer 25,000# x 2 - High Speed	10 Bolt - Oil bath	40 mph	4x8 Tubular	42"	33.5" std / 42" Opt	44" w/600/50x22.5	106.5"	27' 5.5"	20'	Extra Heavy Duty	Standard	Optional	5,670# w/600/50x22.5		600/50x22.5 High Float 425/65X22.5 w/Alum. 11Rx22.5 Dual Wheels	Hydraulic Manual Hydraulic Foot Pedal Air	Optional
XTS22-264+	Tandem w/ suspension	Leaf Spring	48,000#	83" w/600/50x22.5	Tandem - non steer 25,000# x 2 - High Speed	10 Bolt - Oil bath	40 mph	4x8 Tubular	42"	33.5" std / 42" Opt	44" w/600/50x22.5	106.5"	30' 5.5"	22'	Extra Heavy Duty	Standard	Optional	5,800# w/600/50x22.5		600/50x22.5 High Float 425/65X22.5 w/Alum. 11Rx22.5 Dual Wheels	Hydraulic Manual Hydraulic Foot Pedal Air	Optional
HFX28-336	Tandem w/ suspension	Leaf Spring	56,000#	98" w/710/50x26.5	Tandem - non steer 25,000# x 2 - High Speed	10 Bolt - Oil bath	40 mph	4x8 Tubular	34.5"	33.5" Std	53 1/2" w/710/50x26.5	128"	35' 4"	28'	Extra Heavy Duty	N/A	Standard	8,160# w/710/50x26.5		710/50 x 26.5 Radials	Hydraulic Manual Hydraulic Foot Pedal	Optional