# CELLCA S SER

20 HP Sub-Compact Tractor

MORE POWER, PERFORMANCE & VALUE



WORLD'S #1 SELLING TRACTOR

Mahindra
TOUGHEST
TRACTORS
ON EARTH



# **TOP 5 MAJOR ADVANTAGES**

#### **mCOMFORT** ™ **SEAT**

 Extra padding with integrated armrests and retractable belt for ultimate operator comfort

#### **ENGINE DISPLACEMENT**

 30% + larger displacement with lower operating RPM than the closest competition for quieter operation and a longer life

#### **LARGE INDUSTRIAL TIRES**

 Excellent traction and less turf damage in wet applications than bar tires in wet applications

#### **HIGHEST BUILT-IN WEIGHT**

 Heavier components allows for better traction, safety, and stability

# 7 YEAR LIMITED POWERTRAIN WARRANTY SEE MAHOOM MARRANTY POLCY FOR DEPART.

3000 HOURS.
NO DEDUCTIBLE.
REST IN THE INDUSTRY



# MAHINDRA ADVANTAGE ENGINE

- 3 Cylinder Yanmar High Pressure IDI (T4 Final)
- Rated at 3,000 RPM lower RPM than competitors
- Higher torque and fuel efficiency
- Quieter, lower operating RPM extends engine life
- 4 inch Air Cleaner protects engine from debris
- Higher engine displacement at 60.6 cubic inches

#### MAHINDRA ADVANTAGE

## CAB

- Standard Equipment includes: Cab heater, Front and Rear lights, Mirrors and front windshield
- Wide opening doors on left and right
- Excellent visibility to mower deck and loader





#### MAHINDRA ADVANTAGE

# PTO & 3-PT HITCH

#### **PTO**

- Independent PTO
- 540 RPM Rear PTO at 2893 engine RPM
- 2500 RPM Mid PTO at 2875 engine RPM

#### 3-Point Hitch

- Competitive hitch capacity; category 1(N) with a hitch lift capacity of 1,100 lbs.
- Allows usage of a wide variety of implements
- Max Total Flow 7 (GPM)
- 3-Pt Hitch Inching Control Valve

#### MAHINDRA ADVANTAGE

#### **IMPLEMENTS**

Tiller

Mahindra offers a huge selection of performance matched implements to help you accomplish any task you wish to tackle.

Mowers

Post Hole

Tiller

Box Blade

Diggers

Landscape

Rear Blade

Rock Bucket


Rear Blade

Rake

Snow Blower

Broom

Trailer Mover



Mowers

**Snow Blower** 





# MAHINDRA ADVANTAGE

#### IVIUVVER

- Drive over deck
- Dial height adjustment
- More cutting height range

MOWER MODEL	EMAX 20S M54
Туре	Side Discharge
Cutting Width (in)	54
Cutting Height (in)	1-4
Transport Height (in)	5.12
Lift Linkage Type	Lower Link Lift
Height Adjustment	Dial Gauge
Number of Blades	3
Blade Tip Speed (fpm)	18,000
Weight (lbs)	272
Adjustable Anti-Scalp	4
Wheels	

# MAHINDRA ADVANTAGE MCOMFORT<sup>TM</sup> SEAT

- US designed and manufactured with industry leading comfort and support
- Retractable seat belt for greater operator ease of use
- Foldable armrest and recline feature to suit each operator's own preference



#### **MAHINDRA ADVANTAGE**

## **TIRES**

- Front 18x8.5-10, Rear 26x12-12 Available in your choice Ag, Industrial
- Industrial Tires gives you excellent traction and less turf damage than bar tires in wet applications
- Ag Tires for the best grip and pulling power
- Turf tires Front 16x7.5-10, Rear 24x12-12



#### **MAHINDRA ADVANTAGE**

# LOADER

- Excellent lift and reach
- Standard front guard
- Standard Quick Attach loader
- Standard Quick Attach Bucket
- Standard Two Bucket cylinders not just one

Loader model name	23L
Max Lift Height (to pivot pin)	71.3
Clearance with bucket dump (in)	53.9
Max Reach Lift Height (in)	28.3
Max rollback angle (deg)	40
Reach w/bucket on ground	48
Digging depth (in)	5.3
Lift capacity to max height	617
Breakout force at ground level, pivot pin (lb)	1,235
QA Loader	Standard





A variety of attachments are available for the skid steer style bucket quick attach.





	eMax 20S HST	eMax 20S HST CAB
ENGINE:		
Displacement inch³ (cc)	60.6 (993)	60.6 (993)
Engine HP (KW) @ rpm	19.4 @ 3000	19.4 @ 3000
Number of Cylinders	3	3
PTO HP (kw)	14.2 (10.6)	14.2 (10.6)
ELECTRICAL:		
Battery Capacity	12V 450 CCA	12V 450 CCA
Alternator	12 Volt 45 Amps	12 Volt 45 Amps
TRANSMISSION:		
Туре	HST - 2 range	HST - 2 range
No. of speed	Infinite	Infinite
STEERING:		
Туре	Hydrastatic	Hydrastatic
Pump Output (gallons per minute)	2.11	2.11
BRAKES:		
Туре	Wet Disc	Wet Disc
POWER TAKE OFF:		
PTO RPM @ Rated RPM	540 @ 2893	540 @ 2893
Mid	2500 @ 2875	2500 @ 2875
HYDRAULICS:		
Max Total Flow (GPM)	6.97	6.97
Category, 3 Point Hitch	1	1
Hitch Lift Capacity (lbs)	1100	1100
Lift Control Type	Position	Position
Loader Joy Stick Valve	with loader	with loader
DIMENSIONS:		
Min. Ground Clearance	8.3	8.3
Overall Height	86.6	86.6
Overall Length	94	94
Overall Width	44.5	44.5
Weight	1499	1800



We have tripled the size of our parts operation to a 120,000 square foot warehouse, which currently offers more than 40,000 items. The expansion supports and fuels our growth from order placement to shipment with same or next day shipment on all orders. In addition, the Mahindra Parts Catalog System offers 24/7 look-up and order online or via mobile app. Our product range includes spare parts for tractors, attachments and utility vehicles, plus numerous competitive items, such as lubricants, fuel additives, chemicals, anti-freeze, canopies, glopower, oil & filter service packs, radios and hitch parts.







# 2003 DEMING APPLICATION PRIZE 2007 JAPAN QUALITY MEDAL

The Deming Application Prize is considered the Nobel Prize for manufacturing, the farming equipment sector of Mahindra & Mahindra received the honor for establishing Total Quality Management in all business operations in 2003. Mahindra was awarded the Japan Quality Medal for excellence in 2007 for customer focus, overall quality, and business processes - the first tractor company to receive the honor.

For more information, go to: