

PULL TYPE SNOWBLOWERS	1 auger only			
	N74-240INV	N82-260HINV	N92-280HINV	N102-310HINV
Recommended horsepower (HP PTO)	25 @ 40	40 @ 65	60 @ 85	85 @ 120
Cutting width	74"	82"	92"	102
Cutting height	30 ¼"	28 ½"	31 5/8"	37"
Impeller RPM	540	540	540	540
Impeller diameter	24"	26"	28 ½"	31
Impeller depth	9"	11"	12"	14 ¼"
Number of blades	4	4	4	5
Impeller shaft diameter	1 9/16"	1 9/16"	1 9/16"	2"
Balanced impeller	Std	Std	Std	Std
Drum center height	15 ½"	14 ½"	16 ¼"	18 ½"
Removable rotary drum	-	-	-	-
Cylinder for chute	2" X 4"	2" X 4"	2 ½" X 8"	2 ½" X 8"
Chute rotation by hydraulic motor	Std.	Std.	Std	Std
Manual deflector	Std	Std	Std	Std
Hydraulic deflector	Opt.	Opt.	Opt.	Opt.
Semi industrial chute (2 deflectors)	Std	Std	Std	Std
Hydraulic telescopic chute	-	-	-	-
Main auger diameter	17"	17"	18"	22"
Hoses holder	Std	Std	Std	Std
Balanced auger	Std	Std	Std	Std
Reversible carbon steel blade	Std	Std	Std	Std
Reversible Hardox 450 blade	Opt.	Opt.	Opt.	Opt.
Reversible Stainless steel blade	Opt.	Opt.	Opt.	Opt.
Tivar blade	Opt.	Opt.	Opt.	Opt.
Adjustable carbon steel skid shoes	Std	-	-	Std
Adjustable Hardox 450 skid shoes	Opt.	Opt.	Opt.	Opt.
Adjustable Stainless steel skid shoes	Opt.	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.	Opt.
Storage foot	Std	Std	Std	Std
Driving chain	60	60	80	80
Number of safety bolts	2	2	2	3
Bearing ductile iron casing	Std	Std	Std	Std
Shaft P.T.O. standard	T40 long	T60 long	T60 long	T80 long
Hitch category	1	1 & 2	2	2
Approx. weight (lb) - 1 auger	836	900	1 325	1 850

➤ The weight does not include chute and accessories. Specifications are subject to change without notice