

This versatile unit rakes stones and debris to either side or straight ahead for easy pickup. The aggressive teeth on the large-diameter rotor pulverize soil like an ordinary tiller, with the benefit of faster ground speed. The counter-rotating rotor moves soil ahead of it as it tills, filling in low spots and chewing off high spots. It creates perfect seedbeds and windrows. The Utility Soil Conditioner separates rocks, tears up sod, and pulverizes dirt clods. We rake and till deeper than any of our competitors – as deep as 4".



Larger 10" rotor moves a higher volume of dirt than the competition.

FEATURES

- · Direct-drive motor turns large 10" rotor
- Tungsten carbide teeth
- Power angling (optional)
- · Large solid rubber tires





SPECIFICATIONS / OPTIONS

Model	RSC72	RSC84
Part Number	900533	900535
Rotor Width	72"	84"
Overall Width	79.5"	91.5"
Angling	manual 25°	manual 25°
Hydraulic Angling	optional	optional
Wheels/Tires	18" x 8.50"	18" x 8.50"
	Solid Rubber	Solid Rubber
Teeth	88 Carbide Tipped	104 Carbide Tipped
Recommended Hyd. Flow	15 – 33 GPM	15 – 33 GPM
Mounting Plate	universal	universal
Operating Weight (RSC)	1,100 lbs.	1,200 lbs.
Operating Weight (FSC)	1,150 lbs.	1,250 lbs.
Options		
Hydraulic Power Angling		
Wing Kit		
Pistol Grip Control Harness*		
Loader Specific Wire Harness*		
Factory Installed Couplers		

^{*} Applies to Hydraulic Model Only

FAT•N | Char-Lynn



Direct drive motor gives higher production with lower maintenance



Optional:

Wire harness for hydraulic models with attachment controls. Fits Cat/ASV (8-pin) and John Deere/New Holland/CASE/ Bobcat (14-pin)



Optional:

Pistol Grip Control Harness is required if skid steer is NOT equipped with attachment control system. (Only needed when ordering hydraulic angling model).

