Mahindra 60000 series

65 & 75 HP Tractor

MORE POWER, PERFORMANCE & VALUE

WORLD'S #1 SELLING TRACTOR





NO DIESEL PARTICULATE FILTER

 Eliminates lost time, maintenance and high heat for better overall operator comfort

EPS TRANSMISSION

 Standard 15X15 Electronic Power Shuttle allows for a wide speed range and excellent directional control for heavy-duty loader work

540E PTO

 Economy PTO setting allows for less fuel consumption, and lower noise levels in light PTO work

3 POINT LIFT POWER

 Best-in-class lift capacity allows for a wide range of implement attachment possibilities

BUILT STRONG

 Largest tires, heaviest standard weight, and longest wheelbase in class means outstanding durability and excellent operator comfort



3 Cylinder mCRD[™] High Pressure Common Rail Tier IV Final

- Long-lasting, easy to service wet-sleeved, intercooled and turbocharged
- Fed from an oversized 23.8 gallon fuel tank; run longer and get more work done
- Preheat starting aid as standard

mCRD[™] with no Particulate filter:

- Eliminates High heat
- Eliminates High maintenance
- Eliminates High operator involvement
- Eliminates wasted fuel due to NO regeneration cycle

JUST GET ON & GO!

mahindra advantage

- U.S. designed and manufactured with industry leading comfort and support
- Retractable seat belt for greater operator ease of use
- Foldable armrest and recline feature to suit each operator's own preference
- Vinyl covering on open station models for excellent durability in the elements includes standard adjustable mechanical suspension
- Cloth covering on cab models with standard adjustable air ride suspension



MAHINDRA ADVANTAGE

- Electronic Power Shuttle with 15 Forward and 15 Reverse speed options
- Offers best in class versatility for utility farm work
- Smooth engagement in either direction in any range
- 5 gears in each of 3 ranges allows for excellent productivity
- Electro-hydraulic left hand power reverser is excellent for loader work



- Flat deck and ergonomic operator platform
- Spacious and comfortable cab with standard heater and air conditioning
- Wide opening doors on left and right
- Excellent visibility to loader
- Standard rear-view mirrors on left and right side
- Front window wiper is standard (optional rear)

MAHINDRA ADVANTAGE

- The one-piece tilting hood allows easy access to common service items
 - Easily unlocked via a pull lever and raises to 80° upward



Rear Blade

MAHINDRA ADVANTAGE TO & 3-POINT HITCH

PTO

- Independent PTO with electro hydraulic activation for easy use
- Lever for engagement for 540E PTO is conveniently located to left of the operators seat and is standard equipment
- Low 1993 RPM engine speed for standard 540 PTO or 1470 RPM for 540E PTO operation for lower fuel usage

3-Point Hitch & Hydraulic:

- Completely new hydraulic system with best in class 4850 lbs. of lift capacity
- Over 11 GPM of implement pump flow available to power implements quickly
- 2 standard hydraulic remote outlets with a 3rd valve optional
- Standard Cat I & 2 compatible 3-Point with telescopic flexible links
- Easy to adjust 3-Point hitch stabilizers hold implements firmly in place
- Standard Draft control for better productivity

MAHINDRA ADVANTAGE IMPLEMENTS

Mahindra offers a huge selection of performance matched implements to help you accomplish any task you wish to tackle.

- Mowers
- Post Hole Diggers
- Bale Spear Disc Mower

Trencher

 Box Blade Rear Blade

Snow Blower

- Grapple Bucket
 - 4 in 1 Bucket
 - Rock Bucket
- Plus much more...



Snow Blower







- Modern-looking curved boom
- Big 9' dig depth
- 18" bucket standard
- Mechanical thumb optional
- 4 Point Mount System for easy hook up & removal
- Easy to operate controls
- Spacious and comfortable platform
- Protected grease points for long service life
- Designed and tested for the 6000 Series

SPECIFICATIONS	65B	
Maximum Digging Depth (in.)	112	
Digging Depth 2ft Flat Bottom (in.)	110	
Digging Force-Bucket (lbs.)	3895	
Digging Force-Dipper (lbs.)	2358	
Shipping Weight (lbs)	1100	



INDUSTRIAL TIRES



Ask your dealer about big savings when you add Mahindra Implements with your New Mahindra tractor

MAHINDRA ADVANTAGE TIRES

- Wider front Ag tires (9.5LX15) on two wheel drive than the competition
- All 4WD models have taller (16.9X30) tires for better stability and lower compaction
- Large Industrial Tires Available for excellent traction and less turf damage than bar tires in wet applications.

	6065 (2WD)	6065 (4WD)	6065 (CAB)	6075 (4WD)	6075 (CAB)		
Ag (Front/Rear)	11.2-24 / 16.9-28	11.2-24 / 16.9-30					
Industrial (Front/Rear)		12.5/80-18 / 19.5x24					



- Standard Skid steer style coupling system for ultra fast attach/detach of loader implements
- New valve allows operator to perform two loader functions at a time such as raise & level
- Casted bracket components allow a precision fit to the loader
- Forged and casted bucket cylinder linkages improves appearance and performance
- Heavy-duty Grill Guard to protect your investment
- Optional Hydraulic Self-Leveling
- Optional 3rd function valve

U-Flex Joystick with Integrated (2) Buttons:

- Disable Hydraulic Self-Leveling (if equipped)
- Enables 3rd function (*if equipped*)



SPECIFICATIONS	6075L
Maximum Lift Height (in.)	133
Digging depth (in.)	5.5
Lifting capacity to full height at pivot pin (lbs.)	3550
Breakout force (lbs.)	5000
Shipping weight (lbs.)	1880

	6065 2WD	6065 4WD / 4W	/D with Cab	6075 4WD /	4WD with Cab	
ENGINE:						
Number of Cylinders		3	;			
Engine HP @ rpm	62	@ 2100		71 @	2100	
Туре	Four stroke, turbocharged, inte	rcooled, common rail with US Fina	-	water cooled dies	sel engine, comply	
Cylinder Sleeve		Wet Rep	laceable			
Displacement (in ³)		161.	6 in³			
Exhaust System	DOC / under hood r	nuffler / up swept sile	ncer aligned to F	RH A-post on cab	models	
ELECTRICAL:						
Battery	12V, 104A Battery;	Mobile charger & 7-P	ole trailer socket	to suit ASABE sta	ndard;	
Alternator	12V, 55A Alternator; 12	V, 3.6 kW re-engaged	solinoid type, ke	y start with safety	/ interlock;	
CLUTCH:						
Туре	Power shuttle with torsional damper (wet)					
TRANSMISSION:						
No. of Speeds	15 forward, 15 reverse with power shuttle shift, high, low & medium selection lever and foot operated differential lock					
STEERING:						
Туре	Hydrostatic Power steering, with tiltable steering column					
BRAKES:						
Туре	0	il immersed brakes; Le	ever type parking	g break		
POWER TAKE OFF:						
Туре	2 speed independent single lever PTO (wet clutch)					
РТО НР		53.5			61	
PTO RPM @ Rated RPM		540 @ 1993 &	540E @ 1469			
Operation		Solenoid operat	ed push button			
HYDRAULICS:						
Туре	Open center with p	osition and draft cont	rol, telescoping,	stabilizers and fle	x links	
Total Pump Output, Main (GPM)	11.1					
Total Pump Output, Steering (GPM)	4.6					
Hydraulic Outlets	Double spool valves with integrated float (3rd optional)					
3 Point linkage	CAT 1 & 2					
3 Point Lift Capacity (lbs.)	4850					
DIMENSIONS:						
Overall Height (in.)	104	105	114	105	115	
Overall Width (in.)	73.15	73.15		78.74		
Tread Width	Front 62 (standard), 66, 70 & 74, Rear 60 (standard), 64, 68 & 72					
Turning Radius	With brakes 139.76 ± 0. 79 With brakes 149.61 ± 0. 79 With brakes 149.61 ± 0. 79 Without brakes 153.54 ± 79 Without brakes 165.35 ± 0.79 Without brakes 165.35 ± 0.79					
Weight (lbs.)	6096	6746	7495	6746	7495	
Wheelbase (in.)	84.65 87.4 87.4			7.4		

TOUGH TRACTORS TOUGH TRACTORS TOUGH TRACTORS BUILT TO LAST Mahindra

We have tripled the size of our parts operation to a 120,000 square foot warehouse, which currently offers more than 40,000 items. The expansion supports and fuels our growth from order placement to shipment with same or next day shipment on all orders. In addition, the Mahindra Parts Catalog System offers 24/7 look-up and order online or via mobile app. Our product range includes spare parts for tractors, attachments and utility vehicles, plus numerous competitive items, such as lubricants, fuel additives, chemicals, anti-freeze, canopies, glopower, oil & filter service packs, radios and hitch parts.



manufacturing, the farming equipment sector of Mahindra & Mahindra received the honor for establishing Total Quality Management in all business operations in 2003. Mahindra was awarded the Japan Quality Medal for excellence in 2007 for customer focus, overall quality, and business processes - the first tractor company to receive the honor.

For more information, go to:

mahindraUSA.com • mahindraCANADA.com 9020 Jackrabbit Rd., Suite 600 • Houston, Texas 77095 • 877-449-7771 ©2017 Mahindra USA MAH-1117