



MAX SERIES

- #1 Selling Tractor in the World
- 97% Customer Satisfaction Rating
- 7-year Limited Powertrain Warranty
- 98% Customer Loyalty Rating



DEMING PRIZE
2003



JAPAN QUALITY MEDAL
2007

Mahindra
Tractors

VERSATILITY - Max Series

Industry-redefining eco-friendly Tier IV sub-compact and mid-compact models. The backbone of all Max series tractors is a full-length tractor frame that will allow users to install a backhoe at any time. The Max series have a wide range of attachments and implements, including a driver-over mowing deck, snow blowers, blades, brooms and feature the highest capacity loaders in the market.

Key Features:

- Max Versatility – Choose up to 15 implements to handle any task
- Max Maneuverability – Best in class turning radius to get work done in tight spaces
- Max Comfort – Easy turn seat for Tractor – Loader – Backhoe operation, easy on and off with an open platform.

Ideal For:

- Specialty / Hobby Farming
- Rural Lifestyle
- Equine

- Max Stability – Bigger tires, better traction, stability and safety for all jobs
- Max Lift Capacity – Lift more, carry more, pull more and get more done
- Max Engine Performance – 28% lower RPM results in smooth, quiet operation and less fuel consumption
- 7-year limited powertrain warranty*

- Home
- Grounds Maintenance / Municipal

*See Mahindra warranty and your dealer for details



Engine - right side view



Dash panel



Mower

- Easy access to engine and maintenance items
- Lower rated engine rpm, means longer life, less noise, and better fuel efficiency
- Powerful and reliable Mitsubishi engine

- Clear view, easy-to-read instrument panel
- Brilliant backlighting
- Colorful warning lights that quickly inform the operator when service is required

- Drive over deck for easy installation and removal
- Excellent cutting quality
- Available mulch kit

EXCEPTIONAL PERFORMANCE. GREAT VALUE.



Engine - 3 cylinders, four-cycle, indirect-injection, water-cooled diesel

Transmission - HST - 2 ranges (MAX 24) or constant mesh and synchro mesh on F/R shuttle (both available on MAX 26XL)

Hydraulics - Open center, full-lift with position control

Operating Weight - 1,693 to 2,857 lbs. (varies by model) - sturdy, well-built, steel mid-compact chassis

Horsepower - 24.4 - 25.6 (depending on model)

Tires - Ag, industrial or turf

Loader - Lift up to 1,400 lbs. at 82.7" high with the MAX 26L front loader

Warranty - 7-year limited powertrain (See Mahindra warranty and your dealer for details)



Max 24 HST



AVAILABLE IMPLEMENTS


Mahindra offers a huge selection of implements to help you accomplish whatever task you wish to tackle and provide a complete Mahindra experience.

- Wide array of implements (186 variations)
- Competitive financing terms
- Standard-, Medium-, and Heavy-Duty implements to meet your needs
- Implements feature rugged construction with heavy-duty components
- 5-year rotary cutter gearbox limited warranty
- SNOW BLOWERS and SNOW REMOVAL equipment to meet cold-weather needs
- BEST VALUE in the market today



TRACTOR ATTACHMENTS

TRACTOR	MAX 24 HST	MAX 26XL SHUTTLE	MAX 26XL HST	MAX 26XL HST Cab
LOADER	MAX 24L		MAX 26L	
Maximum Lift Height	75"		82.7"	
Clearance with Attachment Dumped	60"		67.3"	
Reach at Maximum Height	23"		29"	
Maximum Dump Angle	38°		32°	
Attachment Rollback Angle	20°		24°	
Digging Depth Below Grade	4"		2.6"	
Lift Capacity to Full Height @ Pivot Pins	900		1402	
Breakout Force @ Pivot Pins	2000		2690	
Rated Flow (Tractor System)	4.6 gpm		4.6 gpm	
Attachment Width	50"		48"	
Attachment Rated Capacity	7 cu. ft.		7 cu. ft.	
Cycle Times @ rpm	2500		2600	
Raise Boom (seconds)	3.7		3.3	
Lower Boom (seconds)	2.6		2.4	
Dump Attachment (seconds)	3.4		2.2	
Retract Attachment (seconds)	2.9		2.6	
Transport Weight (lbs.)	545		627.2	
BACKHOE MODEL		26B		N/A
TRANSPORT				
Transport Height (maximum)		71"		N/A
Transport Overhang		39"		N/A
OPERATIONAL				
Maximum Digging Depth		80"		N/A
Digging Depth (2 Ft.) Flat Bottom		78.5"		N/A
Overall Operating Height - Fully Raised		104.8"		N/A
Loading Height (bucket at 60°)		65"		N/A
Loading Reach (bucket at 60°)		40"		N/A
Reach From Swing Post		102"		N/A
Bucket Rotation		180°		N/A
Swing Arc		150°		N/A
Stabilizer Spread Operating Position		74"		N/A
Stabilizer Down Below Grade		6"		N/A
System Relief Valve Setting (psi)		2000		N/A
Digging Force - Bucket (lbs.)		2270		N/A
Digging Force - Dipper (lbs.)		1248		N/A
Transport Weight (lbs.)		710		N/A



TRACTOR SPECIFICATIONS



TRACTOR	MAX 24 HST	MAX 26XL SHUTTLE	MAX 26XL HST	MAX 26XL HST Cab
ENGINE				
Type	Four-stroke, indirect-injection water-cooled diesel			
Cylinders	3			
Engine HP (kW) @ rpm (EPA Certification)	24.4 (18.2) @ 2500 (T4)	25.6 (19.1) @ 2600		
Compression Ratio	22:1			
Displacement cubic inch ³ (cc)	80.4 (1318)			
Fuel Tank Capacity	6.1 gallons			
ELECTRICAL				
Battery Capacity	12 volt, 45 amp hours			
Alternator	12 volt, 50 amp hours			
CLUTCH				
Type	Single plate, dry			
TRANSMISSION				
Type	HST - 2 ranges	Synchro mesh F/R shuttle and constant mesh on gear shift	HST - 2 ranges	
Number of Gears / Speeds	Infinite	8F / 8R	Infinite	
STEERING				
Type	Hydrostatic Power			
Pump Output (gallons per minute)	2.7			
BRAKES				
Type	Wet disc			
HYDRAULIC SYSTEM				
Type	Open center, full live hydraulic with position control			
Pump Output (gallons per minute)	4.6	5.8		
3-Point Linkage	Category 1, with check chains			
Lift Capacity (lbs.)	1400	2205		
Rear Auxiliary Remote Valves	1 spool optional			
PTO				
Type	Live	Trans	Live	
PTO RPM (engine rpm)	540 @ 2376			
Mid PTO RPM (engine rpm)*	2000 @ 2556	2000 @ 2526		
PTO HP (kW)	19.5 (14.4)	21.5 (16)	20 (14.9)	
OPERATING WEIGHT				
Total (lbs.)	1693	1819	1863	2587
DIMENSIONS with Ag Tires				
Overall Length Inches (mm)	104.1 (2645)	109.3 (2775)		
Overall Width Inches (mm)	50.7 (1290)	54.3 (1380)		
Overall Height Inches (mm) [with Industrial Tires]	81.5 (2070)	84.3 (2140)	82 (2082)	
Turning Radius Min. Feet (meters)	7.2 (2.2)	6.6 (2.0)		
TIRES Sizes and Options				
Ag (Front / Rear)	6x12 / 9.5x16	7x12 / 9.5x16		
Industrial (Front / Rear)	20x8-10 / 27x12.5-15	23x8.5-12 - 12x16.5		
Turf (Front / Rear)	20x8-10 / 29x12.5-15	23x8.5-12 / 33x12.5-16.5		

Specifications and design subject to change without notice.

9020 JACKRABBIT RD., Suite 600 • Houston, Texas 77095 • 877-449-7771

MahindraUSA.com • MahindraCanada.com

© 2017 Mahindra N.A. MAH-0717 MAH54MAX