

Art's Way

Since 1956

NEW

V200/220/240 Manure Spreaders

The V240 offers high capacity in a pull behind option.



700/40/22.5 flotation tires provide less field compaction and smooth pull.



Mechanical Vertical beaters give you the spreading power and path width you are looking for.



**Manure/Material
Spreaders**

www.artsway-ag.com

Features • Specifications

Capacities	V200	V200 w/ Manure Extension	V220	V220 w/ Manure Extension	V240	V240 w/ Manure Extension
Struck Capacity in Cubic Feet	490	630	539	693	588	756
Struck Capacity in Bushels	394	506	433	557	472	607
Heaped Capacity in Cubic Feet	774	914	852	1006	929	1097
Heaped Capacity in Bushels	622	735	684	808	747	882
Inside Box Dimensions						
Length	20 ft.		22 ft.		24 ft.	
Width	7 ft.		7 ft.		7 ft.	
Height	3-1/2 ft.	4-1/2 ft.	3-1/2 ft.	4-1/2 ft.	3-1/2 ft.	4-1/2 ft.
Overall Dimensions						
Height	104-1/4 in.	116-1/4 in.	104-1/4 in.	116-1/4 in.	104-1/4 in.	116-1/4 in.
Weight	16,500 lbs.		17,250 lbs.		18,000 lbs.	
HP Requirements	200 HP		250 HP		300 HP	

Performance specs:

Vertical Beaters:

- Two 42 in. Diameter vertical beaters, covering 7 ft. Height x 7 ft. Width
- 420 rpm, mechanically driven with V-belt drive from tractor PTO
- Beater assembly easily removable for forage operations
- Case-hardened teeth - optional

Floor:

- 1/2 in. Heavy duty UHMW plastic

Slop Gate:

- Hydraulically operated, operator selectable positioning
- Designed to use for both manure and forage

Apron:

- Triple aprons with 667K pintle chain
- Dual hydraulic drive, 20 gpm @ 300psi for manure, 60 gpm forage
- Safety interlocked to prevent movement prior to slop gate activation
- High Speed Clean out

Finish:

- Chemically etched metal to remove all mill scale and contaminants, insuring better paint adhesion
- Dual coated with plural component primer and top-coat for long lasting finish



Art's Way Manufacturing Co., Inc.
 PO Box 288 • Armstrong, IA 50514
 (712) 864-3131 • Fax (712) 864-3154
 sales@artsway-mfg.com
 www.artsway-ag.com
 www.artsway-mfg.com

Art's Way Manufacturing Co. Inc. reserves the right to change design or specifications without notice. Information contained herein is general and is not intended for specific application purposes. Photographs contained herein may be displayed with safety shields and/or guards removed to show mechanical functions only.
 AW-MS217