# amaverick x3 x mr turbo

## DEFIANT

- Trademark Can-Am DNA with next generation design
- Low seating position
- Ergo-Lok cockpit with fourway adjustable seats

## **POWERFUL**

- 120 hp turbocharged Rotax® ACE engine
- Advanced airflow dynamics
- QRS-X transmission

## **PRECISE**

- TTX suspension with industry leading travel
- Ultra efficient and lightweight chassis
- Sharpest handling features

#### SPECIFIC TO X mr PACKAGE

- 64-in. (162.5 cm) wide
- Strategically positioned engine air intake and CVT air intakes / exhaust Smart-Lok™\* Full lockable on-the-fly front differential with electronically-controlled automatic
- 14-in. aluminum wheels with 30-in. ITP Cryptid tires
- Front and rear 18-in. of suspension travel
- FOX<sup>†</sup> 2.5 PODIUM Piggyback shocks with QS3<sup>†</sup> compression adjustment
- 4,500-lb (2,041kg) winch with synthetic rope
- Front bumper, full High Molecular Weight (HMW) skid plate, half-doors, front and rear tow hooks



Carbon Black & Sunburst Yellow / TURBO

ENGINE	TURBO		
Туре	120 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled, Donaldson† high- perfomance air filter and strategically positioned engine air intake		
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		
Transmission	Quick Response System X (QRS-X) CVT, high airflow with strategically positioned CVT air intakes and exhaust, L / H / N / R / P		
Drive Train	Lockable front differential with exclusive Smart-Lok* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD MUD / 4WD TRAIL *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry		
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)		
SUSPENSIONS			
Front Suspension	Double arched A-arm with sway bar / 18-in. (45.7 cm) travel		
Front Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment		
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links / 18-in. (45.7 cm) travel		
Rear Shocks	FOX† 2.5 PODIUM Piggyback with QS3†compression adjustment and bottom-out control		
BRAKES			
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers		
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers		

TIRES / WHEELS				
Front Tires	ITP Cryptid 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)			
Rear Tires	ITP Cryptid 30 x 11 x 14 in. (76.2 x 27.9 x 35.6 cm)			
Wheels	14-in. (35.6 cm) cast-aluminum			
<b>DIMENSIONS</b> A	CAPACITIES			
LxWxH	133 x 66.7 x 66.1 in. (337.8 x 169.4 x 167.9 cm)			
Wheelbase	102 in. (259.1 cm)			
Ground Clearance	14 in. (35.6 cm)			
Estimated Dry Weight	1,653 lb (749.8 kg)			
Cage / Chassis	Dual-phase 980 steel, fully welded			
Rack Capacity	200 lb (91 kg) with LinQ™ quick- attach			
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)			
Fuel Capacity	10.5 gal (40 L)			

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport / ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Protection	Front bumper, full High Molecular Weight (HMW) skid plate, half-doors, front and rear tow hooks
		Instrumentation	Lighter type DC Outlet in central console
		Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	4,500-lb (2,041 kg) winch with synthetic rope	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button
WARRANTY			

Factory 6-months limited warranty Up to 30 months B.E.S.T. coverage Extended





Can-AmOffroad.com

