## **©OUTLANDER™ X™ xc**

## HIGHLIGHTS

- Rotax® V-twin engine
- Intelligent Throttle Control (iTC™) with riding modes
- Front and rear FOX† PODIUM† 1.5 RC2 shocks
- 14-in. cast-aluminum beadlock wheels
- 26-in. ITP<sup>†</sup> Terracross radial tires
- Sport bumper with aluminum pre-runner
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- Front, center & footwell aluminum skid plates
- HMWPE A-arms protectors
- Aluminum taper-profile handlebar with wind deflectors and square pad
- 625-W magneto

- High-strength, multifunction racks with LinQ<sup>™</sup> quick-attach accessory system
- 5.7-gal (21.4 L) water-resistant rear compartment
- Multifunction Analog / Digital gauge
- X package coloration
- Separate front & rear brake controls



Black, Hyper Silver & Sunburst Yellow / 1000R

ENGINE	1000R
Туре	91 hp, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3cm) travel
Front Shocks	FOX† PODIUM† 1.5 RC2
Rear Suspension	Arched double A-arm with front sway bar 9.9 in. (25.1cm) travel
Rear Shocks	FOX† PODIUM† 1.5 RC2

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS	
Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6cm)
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. cast-aluminum beadlock

n)

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Standard
Winch	Prewired for available winch	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Front bumper with pre-runner Aluminum taper-profile handlebar with wind deflectors and square pad Front, center & footwell aluminum skid plates		

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 36 months B.E.S.T. coverage



HMWPE A-arms protectors, mudguards

