



* Shown w/ optional Aluminum Wheels

WIDTH/LENGTH	BASE PRODUCT CODE	MSRP
*5x8	5X80DSA22	
**6x10	6X100DSA30	
**6x12	6X120DSA30	
7x12	7X120DSA30	
7x14	7X140DSA30	

* Standard with 2,200# Axle & ST185/80R13 Tires (GVWR 2,200#)
 ** Standard with 3,000# Axle & ST205/75R14 Tires (GVWR 2,990#)

HIGHLIGHTS

- Perimeter Tube Frame
- 3" x 6" Extruded Alum. Triple Tongue (6' & 7' Wide)
- ATP Fenders w/ Gussets
- Surface Mount LED Lighting
- Pressure Treated Decking
- Fold-In Radius Gate
- Stake Pockets
- 2" x 4" Tube Rear Gate Supports

STRUCTURAL	STANDARD FEATURES		POPULAR OPTIONS			
			MSRP		MSRP	MSRP
Cross Members	2" x 3" Tube 24" OC	16" OC		12" OC		
Frame	2" x 3" Perimeter Tube (5' & 6' Wide) 2" x 4" Perimeter Tube (7' Wide)	2" Uprights ILO 1.5"		Add Extra Upright		
Jack	2,000# Top-Wind Set Back Jack w/ Foot	5,000# Jack w/ Foot		Caster Wheel ILO Foot		
Rear Loading	48" Fold-In Radius Tube Gate	48" Bi-Fold Square Gate ILO Straight		60" Bi-Fold Square Gate ILO Straight		
Sides	1.5" x 1.5" Tube 14" Tall (5' & 6' Wide) 1.5" x 1.5" Tube 15" Tall (7' Wide)	ATP Stone Guard		ATP Skirting .045	24" Sides	
Side Loading	Optional	58" Wide Radius Side Gate		58" Wide Bi-Fold Square Gate		
Tongue	2" x 3" Tube A-Frame (5' Wide) 3" x 6" Extruded Alum. Triple Tongue (6' & 7' Wide)					
Top Rail	2" x 2" Tube					
RUNNING GEAR						
** Axles	2,200# E-Z Lube 4" Drop Spring (5' Wide) 3,000# E-Z Lube 4" Drop Spring (6' Wide) 3,500# E-Z Lube 4" Drop Spring (7' Wide) 1 Idler	Spring 3,500# Brake Axle	5' Wide 6' Wide 7' Wide	Torsion Axle (Idler)	5' Wide 6' Wide 7' Wide	Torsion 3,500# Brake Axle 5' Wide 6' Wide 7' Wide
** Tires/Wheels	ST205/75R14 Nitrogen Filled Silver Mod Steel (6' & 7' Wide)	ST205/75R14 Spare Tire	Alum-Steel	Spare Mount		Aluminum Wheels Upgrade
FLOORS						
Floor	Dura Color Radius Edge Deck	Extruded Aluminum				
COMPONENTS						
Coupler	2" A-Frame (5' Wide) 2" Straight (6' & 7' Wide)	2 ^{5/16"} Straight		Adjustable 2 ^{5/16"} Coupler		
Stake Pockets	Included	Additional Stake Pockets				
Tie Downs	Optional	1,000# D-Rings (Installed)		5,000# D-Rings (Installed)		