

The Perfect Cutter for Rural Grass Maintenance - in a Smooth Top Design.

- Smooth top for easier cleaning
- Floating top link for following ground undulations
- ASAE Category 3 driveline
- Fully welded deck
- Available rubber or chain guards - front and rear
- High blade tip speed
- 84" Features single or dual tailwheel option



	RCF2060	RCF2072	RCF2084
Horsepower	20-65 HP		45-90 HP
Hitch	Cat. 1 - Floating Top Link		Cat. 1 & 2 Floating Top Link
	Clevis Type Lower Links, Quick Hitch Adaptable		
Working Width (cm)	60 (152)	72 (183)	84 (213)
Weight - lb (kg)	620 (281)	745 (338)	Sgl tailwheel: 1,370 (621) Dual tailwheel: 1,500 (680)
Cutting Height	1-1/2" - 12"		
Cutting Capacity	2"		
Deck	All Welded		
Deck Thickness	10 Gauge		
Deck Height	9-11/16"	11"	11-15/16"
Safety Guards	Rear Metal Banding - Standard		
Optional Guarding	Front: Rubber or Chain Rear: Rubber or Chain		
Skids	Weld-on (Bolt on Accessory Skid Shoes Available)		
Blades	2 ea. (1/2" x 3" Heat Treated) Free Swinging High-Lift		2 ea. (1/2" x 4" Heat Treated) Free Swinging High-Lift
Blade Bolt	Keyed w/Hardened Flat Washer & Lock Nut		
Blade Speed	16,363 fpm	14,955 fpm	17,113 fpm
Dishpan	Round, 10 Ga. x 24" Dia., Dish Shaped		Oval, 3/16" x 27"
Gearbox Rating	65 HP	65 HP	90 HP
Gearbox	540 RPM, Beveled Gears, Cast Iron Housing		
Driveline	ASAE Cat. 3; Shear Bolt or 2-Plate Slip-Clutch		ASAE Cat. 4; 2-Plate Slip-Clutch
Tailwheels	4" x 15" Laminated Tire or 4" x 16" Molded Rubber - 360 Degree Swivel		Single or Dual 4" x 15" Laminated Tire w/ Cast Iron Hub - 360 Degree Swivel

See dealer for complete warranty information.

