

Frontier Rear Blades



Medium-Duty • Medium-Plus • Heavy-Duty • Heavy-Plus • Hydraulic

Details – Frontier Rear Blades

From light utility work to heavy grading, Frontier Rear Blades are an easy and affordable solution for material handling. Whether you're shaping ground or working on professional landscaping, you can choose from four duty classes – medium, medium-plus, heavy, and heavy-plus – and 18 different models to meet your needs.

Available in working widths from 5- to 10-feet, Frontier Rear Blades match well with tractors up to 160-horsepower (2-wheel drive) or 145-horsepower (4-wheel drive). A reinforced tubular steel frame helps you take on tough applications. The dozer-type, full-radius moldboard is professional grade to handle heavy loads. And cutting edges are reversible to give your blade twice the work life. Let's face it – these are no-nonsense blades, built rugged to withstand the most demanding chores.

But they're not just tough. **Frontier Rear Blades are also adaptable to your conditions.** A 360-degree swing angle lets you customize the blade to your job. Go with the offset, angle, and tilt features to make adjustments in minimal time.

The Frontier Rear Blades are sold and supported by John Deere, the most trusted name in farm, ranch and lawn equipment. To help you choose the right Frontier Rear Blade, talk to your local John Deere dealer, your exclusive source of Frontier Equipment.

www.BuyFrontier.com



End plates (optional) hold in extra material while dragging it from one place to another, making it an ideal feature for filling.



Skid shoes (optional) protect the moldboard cutting edge from hitting low-lying obstructions while cleaning corrals or removing snow.



The turntable on the RB21 and RB22 Series allows you to adjust the angle to three different positions in both forward and reverse.



With the RB23 and RB24 Series, you control the offset, angle, and tilt adjustments – all from the comfort of your tractor seat.



Frontier now offers hydraulic capacity on a medium-duty rear blade with the RB21H Series. You can now adjust blade angle from your operator station, a feature not available before on a rear blade of this duty class.

ing, ditching, snow removal, and a whole lot more

Pick The Right Duty For The Job

It's great to have options

You're sure to find the right rear blade for your operation with Frontier's wide range of multi-purpose scraper attachments. Built for high hours of usage in tough, gritty applications, the Frontier Rear Blades offer choices for simple and not-so-easy chores alike. Just select the model that's best for your particular job. For your convenience, we've provided an overview of each of our five series to better illustrate what line of rear blades is best suited for a given chore.

But regardless of what rear blade you choose, you can be certain that each one comes with a few standard features – built-in durability, high-performance, and affordability. Plus, they're ready to work when you are...job-to-job, and season-to-season. Whether you're doing road repair in the spring, after a hard-hitting, stormy winter, or landscaping around the home in the summer. If there's a job to be done, Frontier has your 'do-it-all' options.



21H Series Medium-Duty Hydraulic Rear Blades – compatible with tractors up to 50 horsepower. Designed for minor road repair and light material handling. Equipped with hydraulic angle adjustment, eliminating the need for operators to manually adjust blade angle to adapt to multiple tasks.



21 Series Medium-Duty Rear Blades – compatible with tractors up to 65 horsepower. Ideal for light road maintenance, lawn care, gardening, and other light-duty landscaping. Also great for year-round ground leveling, roadside clearing, and snow removal. Available with manual adjustments only. *(Shown with optional skid shoes and end plates.)*



22 Series Medium-Duty-Plus Rear Blades – compatible with tractors up to 80 horsepower. Perfect for leveling, gardening, road maintenance, and cleaning feedlots. The blade design allows you to cut and roll the soil rather than drag it, saving you time, horsepower, and fuel. Manual adjustments are standard; hydraulic offset adjustment is optional.

Have A Long List Of Chores Ready



23 Series Heavy-Duty Rear Blades – compatible with tractors up to 120 horsepower. Features rugged construction for ditching and terrace building. Manual adjustments are standard. Or, to complete your work quickly and easily, go with the optional hydraulic adjustments for tilt, offset, and angle. *(Shown with optional full hydraulic controls, skid shoes and end plates.)*



24 Series Heavy-Duty-Plus Rear Blades – compatible with tractors up to 160 horsepower. Built extra tough for a wide range of material handling...from landscaping to heavy-duty dam-building. The enhanced curved moldboard gives you maximum penetration and added precision to cut and roll the soil rather than drag it. Hydraulic angle adjustment is standard; fully hydraulic controls are optional. *(Shown with optional full hydraulic controls and end plates.)*

How will you use your Frontier Rear Blade?



Up to the task

No matter the conditions – indoor, outdoor, or the elements – Frontier Rear Blades fit the job. With five rugged series to choose from, you get the versatility and performance you need to tackle just about any chore. From cleaning out a poultry house, to leveling driveways, to clearing snow from your property, Frontier Rear Blades move material effectively from start to finish.

Specifications

Model	RB2160H	RB2172H	RB2184H	RB2196H
Angle, tilt, & offset adjustments	Hydraulic angle manual tilt offset	Hydraulic angle manual tilt offset	Hydraulic angle manual tilt offset	Hydraulic angle manual tilt offset
Hitch compatibility	Category 1 (iMatch™ compatible)	Category 1 (iMatch compatible)	Category 1 (iMatch compatible)	Category 1 (iMatch compatible)
Grading & leveling	Fine, precision grading & leveling	Fine, precision grading & leveling	Fine, precision grading & leveling	Fine, precision grading & leveling
Moldboard	0.25 in. (6 mm) full-radius moldboard	0.25 in. (6 mm) full-radius moldboard	0.25 in. (6 mm) full-radius moldboard	0.25 in. (6 mm) full-radius moldboard
Frame	Formed steel channel frame	Formed steel channel frame	Formed steel channel frame	Formed steel channel frame
Cutting Edge	0.5 x 6 in. (1.3 x 15.2 cm), reversible	0.5 x 6 in. (1.3 x 15.2 cm), reversible	0.5 x 6 in. (1.3 x 15.2 cm), reversible	0.5 x 6 in. (1.3 x 15.2 cm), reversible
Angle/pivot	360°	360°	360°	360°
Forward angle positions	up to 40 degrees each side	up to 40 degrees each side	up to 40 degrees each side	up to 40 degrees each side
Reverse angle positions	up to 40 degrees each side	up to 40 degrees each side	up to 40 degrees each side	up to 40 degrees each side
Tilt positions	up to 40 degrees each side	up to 40 degrees each side	up to 40 degrees each side	up to 40 degrees each side
Moldboard thickness	0.25 in. (6 mm)	0.25 in. (6 mm)	0.25 in. (6 mm)	0.25 in. (6 mm)
Moldboard length	60 in. (152.4 cm)	72 in. (182.9 cm)	84 in. (213.4 cm)	96 in. (243.8 cm)
Moldboard height	15 in. (38.1 cm)	15 in. (38.1 cm)	15 in. (38.1 cm)	15 in. (38.1 cm)
Offset	6 or 12 in. (15.2 or 30.5 cm), left or right	6 or 12 in. (15.2 or 30.5 cm), left or right	6 or 12 in. (15.2 or 30.5 cm), left or right	6 or 12 in. (15.2 or 30.5 cm), left or right
Duty	Medium	Medium	Medium	Medium
Tractor horsepower	2WD: 50 hp (37.3 kW) max.; 4WD: 45 hp (33.6 kW) max.	2WD: 50 hp (37.3 kW) max.; 4WD: 45 hp (33.6 kW) max.	2WD: 50 hp (37.3 kW) max.; 4WD: 45 hp (33.6 kW) max.	2WD: 50 hp (37.3 kW) max.; 4WD: 45 hp (33.6 kW) max.
Parking stand	Standard	Standard	Standard	Standard
Skid shoe bundle	Optional	Optional	Optional	Optional
Operating weight	346 lb. (157.0 kg)	372 lb. (168.7 kg)	398 lb. (180.5 kg)	423 lb. (191.9 kg)
Warranty*	1 year	1 year	1 year	1 year

* Hour and/or usage limitations may apply. See Warranty for new John Deere Agricultural Products at your local dealer for details.

Model	RB2160	RB2172	RB2184	RB2196
Angle, tilt, & offset adjustments	Manual	Manual	Manual	Manual
Hitch compatibility	Category 1 (iMatch compatible)	Category 1 (iMatch compatible)	Category 1 (iMatch compatible)	Category 1 (iMatch compatible)
Grading & leveling	Fine, precision grading & leveling	Fine, precision grading & leveling	Fine, precision grading & leveling	Fine, precision grading & leveling
Moldboard	0.25 in. (6 mm) full-radius moldboard	0.25 in. (6 mm) full-radius moldboard	0.25 in. (6 mm) full-radius moldboard	0.25 in. (6 mm) full-radius moldboard
Frame	Formed steel channel frame	Formed steel channel frame	Formed steel channel frame	Formed steel channel frame
Cutting Edge	0.5 x 6 in. (1.3 x 15.2 cm), reversible	0.5 x 6 in. (1.3 x 15.2 cm), reversible	0.5 x 6 in. (1.3 x 15.2 cm), reversible	0.5 x 6 in. (1.3 x 15.2 cm), reversible
Angle/pivot	360°	360°	360°	360°
Forward angle positions	3, up to 53 degrees each side	3, up to 53 degrees each side	3, up to 53 degrees each side	3, up to 53 degrees each side
Reverse angle positions	3, up to 53 degrees each side	3, up to 53 degrees each side	3, up to 53 degrees each side	3, up to 53 degrees each side
Tilt positions	3, up to 22 degrees up or down	3, up to 22 degrees up or down	3, up to 22 degrees up or down	3, up to 22 degrees up or down
Moldboard thickness	0.25 in. (6 mm)	0.25 in. (6 mm)	0.25 in. (6 mm)	0.25 in. (6 mm)
Moldboard length	60 in. (152.4 cm)	72 in. (182.9 cm)	84 in. (213.4 cm)	96 in. (243.8 cm)
Moldboard height	17 in. (43.2 cm)	17 in. (43.2 cm)	17 in. (43.2 cm)	17 in. (43.2 cm)
Offset	6 or 12 in. (15.2 or 30.5 cm), left or right	6 or 12 in. (15.2 or 30.5 cm), left or right	6 or 12 in. (15.2 or 30.5 cm), left or right	6 or 12 in. (15.2 or 30.5 cm), left or right
Duty	Medium	Medium	Medium	Medium
Tractor horsepower	2WD: 65 hp (48.5 kW) max.; 4WD: 60 hp (44.7 kW) max.	2WD: 65 hp (48.5 kW) max.; 4WD: 60 hp (44.7 kW) max.	2WD: 65 hp (48.5 kW) max.; 4WD: 60 hp (44.7 kW) max.	2WD: 65 hp (48.5 kW) max.; 4WD: 60 hp (44.7 kW) max.
Parking stand	Standard	Standard	Standard	Standard
Skid shoe bundle	Optional	Optional	Optional	Optional
Operating weight	392 lb. (177.8 kg)	422 lb. (191.4 kg)	448 lb. (203.2 kg)	476 lb. (215.9 kg)
Warranty*	1 year	1 year	1 year	1 year

* Hour and/or usage limitations may apply. See Warranty for new John Deere Agricultural Products at your local dealer for details.

Model	RB2272	RB2284	RB2296
Angle, tilt, & offset adjustments	Manual; optional hydraulic offset (up to 1 hydraulic remote required)	Manual; optional hydraulic offset (up to 1 hydraulic remote required)	Manual; optional hydraulic offset (up to 1 hydraulic remote required)
Hitch compatibility	Category 2 (Quick-Coupler compatible)	Category 2 (Quick-Coupler compatible)	Category 2 (Quick-Coupler compatible)
Grading & leveling	Landscaping & moderate grading	Landscaping & moderate grading	Landscaping & moderate grading
Moldboard	Heavy-duty, dozer-type construction	Heavy-duty, dozer-type construction	Heavy-duty, dozer-type construction
Frame	Formed steel channel frame	Formed steel channel frame	Formed steel channel frame
Cutting edge	0.5 x 6 in. (1.3 x 15.2 cm), reversible	0.5 x 6 in. (1.3 x 15.2 cm), reversible	0.5 x 6 in. (1.3 x 15.2 cm), reversible
Angle/pivot	360°	360°	360°
Forward angle positions	3, up to 45 degrees each side	3, up to 45 degrees each side	3, up to 45 degrees each side
Reverse angle positions	3, up to 45 degrees each side	3, up to 45 degrees each side	3, up to 45 degrees each side
Tilt positions	3, up to 23 degrees up or down	3, up to 23 degrees up or down	3, up to 23 degrees up or down
Moldboard thickness	.25 in. (6 mm)	.25 in. (6 mm)	.25 in. (6 mm)
Moldboard length	72 in. (182.9 cm)	84 in. (213.4 cm)	96 in. (243.8 cm)
Moldboard height	19 in. (48.3 cm)	19 in. (48.3 cm)	19 in. (48.3 cm)
Offset	9 or 18 in. (22.9 or 45.7 cm), left or right	9 or 18 in. (22.9 or 45.7 cm), left or right	9 or 18 in. (22.9 or 45.7 cm), left or right
Duty	Medium plus	Medium plus	Medium plus
Tractor horsepower	2WD: 80 hp (59.7 kW) max.; 4WD: 70 hp (52.2 kW) max.	2WD: 80 hp (59.7 kW) max.; 4WD: 70 hp (52.2 kW) max.	2WD: 80 hp (59.7 kW) max.; 4WD: 70 hp (52.2 kW) max.
Parking stand	Standard	Standard	Standard
Skid shoe bundle	Optional	Optional	Optional
Operating weight	738 lb. (333.4 kg)	755 lb. (342.5 kg)	772 lb. (350.2 kg)
Warranty*	1 year	1 year	1 year

* Hour and/or usage limitations may apply. See Warranty for new John Deere Agricultural Products at your local dealer for details.

Model	RB2307	RB2308	RB2309	RB2310
Angle, tilt, & offset adjustments	Manual; optional hydraulic angle, tilt, & offset (up to 3 hydraulic remotes required)	Manual; optional hydraulic angle, tilt, & offset (up to 3 hydraulic remotes required)	Manual; optional hydraulic angle, tilt, & offset (up to 3 hydraulic remotes required)	Manual; optional hydraulic angle, tilt, & offset (up to 3 hydraulic remotes required)
Hitch compatibility	Category 2 (Quick-Coupler compatible)	Category 2 (Quick-Coupler compatible)	Category 2 (Quick-Coupler compatible)	Category 2 (Quick-Coupler compatible)
Grading & leveling	Heavy grading and snow removal	Heavy grading and snow removal	Heavy grading and snow removal	Heavy grading and snow removal
Moldboard	Heavy-duty, dozer-type construction	Heavy-duty, dozer-type construction	Heavy-duty, dozer-type construction	Heavy-duty, dozer-type construction
Frame	Formed steel channel frame	Formed steel channel frame	Formed steel channel frame	Formed steel channel frame
Cutting edge	0.5 x 6 in. (1.3 x 15.2 cm), reversible	0.5 x 6 in. (1.3 x 15.2 cm), reversible	0.5 x 6 in. (1.3 x 15.2 cm), reversible	0.5 x 6 in. (1.3 x 15.2 cm), reversible
Angle/pivot	360°	360°	360°	360°
Forward angle positions	3, up to 45 degrees each side (0-45 degrees each side**)	3, up to 45 degrees each side (0-45 degrees each side**)	3, up to 45 degrees each side (0-45 degrees each side**)	3, up to 45 degrees each side (0-45 degrees each side**)
Reverse angle positions	3, up to 45 degrees each side (0-45 degrees each side**)	3, up to 45 degrees each side (0-45 degrees each side**)	3, up to 45 degrees each side (0-45 degrees each side**)	3, up to 45 degrees each side (0-45 degrees each side**)
Tilt positions	3, up to 23 degrees up or down (0-15 degrees up or down**)	3, up to 23 degrees up or down (0-15 degrees up or down**)	3, up to 23 degrees up or down (0-15 degrees up or down**)	3, up to 23 degrees up or down (0-15 degrees up or down**)
Moldboard thickness	5/16, .3125 in. (7.9 mm)	5/16, .3125 in. (7.9 mm)	5/16, .3125 in. (7.9 mm)	5/16, .3125 in. (7.9 mm)
Moldboard length	84 in. (213.4 cm)	96 in. (243.8 cm)	108 in. (274.3 cm)	120 in. (304.8 cm)
Moldboard height	19 in. (48.3 cm)	19 in. (48.3 cm)	19 in. (48.3 cm)	19 in. (48.3 cm)
Offset	9 or 18 in. (22.9 or 45.7 cm), left or right [0-19 in. (0-48.3 cm), left or right**]	9 or 18 in. (22.9 or 45.7 cm), left or right [0-19 in. (0-48.3 cm), left or right**]	9 or 18 in. (22.9 or 45.7 cm), left or right [0-19 in. (0-48.3 cm), left or right**]	9 or 18 in. (22.9 or 45.7 cm), left or right [0-19 in. (0-48.3 cm), left or right**]
Duty	Heavy	Heavy	Heavy	Heavy
Tractor horsepower	2WD: 120 hp (89.5 kW) max.; 4WD: 110 hp (82.0 kW) max.	2WD: 120 hp (89.5 kW) max.; 4WD: 110 hp (82.0 kW) max.	2WD: 120 hp (89.5 kW) max.; 4WD: 110 hp (82.0 kW) max.	2WD: 120 hp (89.5 kW) max.; 4WD: 110 hp (82.0 kW) max.
Parking stand	Standard	Standard	Standard	Standard
Skid shoe bundle	Optional	Optional	Optional	Optional
Operating weight	1,060 lb. (480.8 kg) [1,162 lb. (527.1 kg)**]	1,139 lb. (516.6 kg) [1,241 lb. (562.9 kg)**]	1,240 lb. (562.5 kg) [1,342 lb. (608.7 kg)**]	1,300 lb. (589.7 kg) [1,402 lb. (635.9 kg)**]
Warranty*	1 year	1 year	1 year	1 year

* Hour and/or usage limitations may apply. See Warranty for new John Deere Agricultural Products at your local dealer for details. **Fully hydraulic model

Model	RB2408	RB2409	RB2410
Angle, tilt, & offset	Manual tilt & offset, hydraulic angle (1 hydraulic remote required); optional hydraulic angle, tilt, & offset (up to 3 hydraulic remotes required)	Manual tilt & offset, hydraulic angle (1 hydraulic remote required); optional hydraulic angle, tilt, & offset (up to 3 hydraulic remotes required)	Manual tilt & offset, hydraulic angle (1 hydraulic remote required); optional hydraulic angle, tilt, & offset (up to 3 hydraulic remotes required)
Hitch compatibility	Category 2/3 (Quick-Coupler compatible)	Category 2/3 (Quick-Coupler compatible)	Category 2/3 (Quick-Coupler compatible)
Grading & leveling	Heavy grading and snow removal	Heavy grading and snow removal	Heavy grading and snow removal
Moldboard	Heavy-duty, dozer-type construction	Heavy-duty, dozer-type construction	Heavy-duty, dozer-type construction
Frame	Formed steel channel frame	Formed steel channel frame	Formed steel channel frame
Cutting edge	0.5 x 6 in. (1.3 x 15.2 cm), reversible	0.5 x 6 in. (1.3 x 15.2 cm), reversible	0.5 x 6 in. (1.3 x 15.2 cm), reversible
Angle/pivot	360°	360°	360°
Forward angle positions	Right: 4, up to 26 degrees; left: 5, up to 38 degrees. (0-43 degrees each side**)	Right: 4, up to 26 degrees; left: 5, up to 38 degrees. (0-43 degrees each side**)	Right: 4, up to 26 degrees; left: 5, up to 38 degrees. (0-43 degrees each side**)
Reverse angle positions	Right: 4, up to 26 degrees; left: 5, up to 38 degrees. (0-43 degrees each side**)	Right: 4, up to 26 degrees; left: 5, up to 38 degrees. (0-43 degrees each side**)	Right: 4, up to 26 degrees; left: 5, up to 38 degrees. (0-43 degrees each side**)
Tilt positions	2, up to 15 degrees up or down (0-12 degrees, up or down**)	2, up to 15 degrees up or down (0-12 degrees, up or down**)	2, up to 15 degrees up or down (0-12 degrees, up or down**)
Moldboard thickness	5/16, .3125 in. (7.9 mm)	5/16, .3125 in. (7.9 mm)	5/16, .3125 in. (7.9 mm)
Moldboard length	96 in. (243.8 cm)	108 in. (274.3 cm)	120 in. (304.8 cm)
Moldboard height	19 in. (48.3 cm)	19 in. (48.3 cm)	19 in. (48.3 cm)
Offset	Right: 0-28 in. (0-71.1 cm); left: 0-26 in. (0-66.04 cm) [0-36 in. (0-91.4 cm) left or right**]	Right: 0-28 in. (0-71.1 cm); left: 0-26 in. (0-66.04 cm) [0-36 in. (0-91.4 cm) left or right**]	Right: 0-28 in. (0-71.1 cm); left: 0-26 in. (0-66.04 cm) [0-36 in. (0-91.4 cm) left or right**]
Duty	Heavy plus	Heavy plus	Heavy plus
Tractor horsepower	2WD: 160 hp (119.3 kW) max.; 4WD: 145 (108.1 kW) hp max.	2WD: 160 hp (119.3 kW) max.; 4WD: 145 (108.1 kW) hp max.	2WD: 160 hp (119.3 kW) max.; 4WD: 145 (108.1 kW) hp max.
Parking stand	Standard	Standard	Standard
Skid shoe bundle	Optional	Optional	Optional
Operating weight	1,451 lb. (658.2 kg) [1,499 lb. (679.9 kg)**]	1,501 lb. (680.8 kg) [1,549 lb. (702.6 kg)**]	1,550 lb. (703.1 kg) [1,598 lb. (724.8 kg)**]
Warranty*	1 year	1 year	1 year

* Hour and/or usage limitations may apply. See Warranty for new John Deere Agricultural Products at your local dealer for details. **Fully hydraulic model



This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL JOHN DEERE DEALER FOR DETAILS. Frontier Equipment reserves the right to change specifications, design and price of products described in this literature without notice. John Deere, the leaping deer symbol, and John Deere's green and yellow trade dress are the trademarks of Deere & Company. Copyright 2011, Frontier Equipment.

www.BuyFrontier.com