



MAXIMIZE YOUR CUT

Are you ready to tackle the tough projects? The TB-Max is ready to cut them down to size.



3 MOUNTING OPTIONS

9 - 14 OR 15 - 20 GPM MOTOR

3" CUTTING DIAMETER

44" CUTTING WIDTH







QUICK SPECS

- Floating Position & 5 Locked Cutting Positions
- Red pin used for easy position adjustment
- Two Motor Options
 - O 9-14 Gallons per Minute
 - 15-20 Gallons Per Minute
- Three Mounting Options Available
 - O Universal Skid Steer
 - O John Deere 200 500
 - C Euro/Quickie/Global
- 44" Cutting Width
- Up to a 3" Cut Capacity
- 3,000lb Tractor Minimum









TB-MAX JR PATENT

Want a front mounted mower built for a smaller tractor?

The TB-MAX JR is ready to go.



2 MOUNTING OPTIONS

9 - 14 GPM MOTOR OPTIONS

3" CUTTING DIAMETER

32" CUTTING WIDTH



TB Power Kit required for tractors with hydraulic pump flow rates under 9 GPM.





QUICK SPECS

- Floating Position & 5 Locked Cutting Positions
- Red pin used for easy position adjustment
- One Motor Options
 - O 9-14 Gallons per Minute
- Two Mounting Options Available
 - O Universal Skid Steer
 - O John Deere 200 500
- 32" Cutting Width
- Up to a 3" Cut Capacity
- 2,000lb Tractor Minimum





ADJUSTMENT BEARINGS

- Automotive Quality Tapered Roller Bearing
- 40,000lb Thrust Load Rating
- Removable and Replaceable Race
- Two Per Unit for Effortless Angle Adjustment

TRUE DIRECT DRIVE SYSTEM

- Genuine Eaton Char-Lynn Hydraulic Motor
- 2 Year Trailblazer Limited Warranty on Hydraulic Motor
- Precision CNC Machined Spindle Hub Assembly.
- High Quality Press Fit Bearings
- Precision CNC Machined 1 3/8" Cold Rolled Output Shaft











BLADES AND BLADE BOLTS

- Flame Hardened Double
 Sided Cutting Edge Blades
- True Hardened Rotary Cutter Blades
- Square Blade Bolts for Maximum Life and Securement

HEAVY BLADE CARRIER

- Bent on 45 Degree Angle for better Airflow and Performance
- Keyed Precision Machined Hub for Maximum Securement
- 3/8" Thick Material with Added Blocks at Blade Securement Locations

FIND OUT MORE ABOUT OUR TRAILBLAZER LINEUP AT

WWW.TRAILBLAZERATTACHMENTS.COM







QUICK SPECS

- Optimized for TB Series Cutters
- Oil sight & temperature gauge on reservoir
- Pressure Relief valve for hydraulic system protection
- Heavy-Duty frame acts as ballast
- 20 Gallon Reservoir Tank
- Pump puts out 11.4 GPM of constant flow (non-adjustable)
- 400 lbs when filled with hydraulic fluid

GIVE YOUR

THE OPTIMUM **CUTTING POWER**







CLEARING PATHS THROUGH INNOVATION



CONTACT US TODAY!

(423) 405 - 5150

Sales@TrailBlazerAttachments.com

TrailBlazerAttachments.com

^{*} Titan Implement is the exclusive distributor of the TrailBlazer Attachments Product Line.