



# 8-ROW PL5500

The PL5500 gives producers a simple, 8-row wing-fold planter with narrow-transport capabilities. Folding to only 9' 9", this planter is easy to maneuver from field to field and is compatible with a wide range of tractors, requiring only 115-drawbar

horsepower (minimum) to pull. With the new 5000 Series row units, the all-new Air-Pro® Meters, and its simple, positive air pressure design, the PL5500 achieves industry-leading singulation and seed placement.



# 8-ROW FRONT-FOLD PL5500

# FEATURES & BENEFITS

## 5000 SERIES ROW UNIT

8-Row	Working Width	Transport Width (Bulk)	Transport Height	Engine H.P. Required	Row Spacing	Base Weight	Seed Capacity	Fertilizer Capacity
PL5500	20' 6"	9' 9"	11' 6"	115+	30"	6,400	1.6- or 3-bu./row	300 gal. or 53 cu. ft. (Opt)

See [www.greatplainsag.com](http://www.greatplainsag.com) for complete specifications.



The 5000 Series row unit utilizes ductile cast parallel arms for long-term row unit stability. 15", 4mm blades turning on 205 triple-lip sealed bearings ensure long life and accurate seed depth. Blades are offset 1/2" to slice residue and form a perfect seed trench. Options include unit-mounted Turbo or fluted coulters, row cleaners, and seed firmers.



## ADDITIONAL STANDARD FEATURES

- 4mm offset opener blades
- Hardened cast blade separator w/ liquid fertilizer tube
- Heavy-duty row unit down-pressure springs (up to 375 lbs./row)
- 4" side-depth wheels
- Clear-Shot® seed tubes
- PM300 monitor included w/ ground-drive units
- Available w/ either 1.6 bu. or 3 bu. hoppers
- LED safety lighting



### CHOOSE A PRESS WHEEL

Choose (l to r) Wedge wheels that pinch the seed trench together but provide a wide footprint, 1"x12" double-v for all-around performance, or spider wheels with drag chains for aggressive closing action of the seed trench.




### 180-DEGREE WING FOLD

Wings fold 180 degrees to provide a narrow transport width of under 10'. This fold design is simple, yet strong, and removes a lot of the expense and complexity of lift-and-twist designs.



### IRC OR GROUND DRIVE

Choose either Individual Row Control (IRC) for consistent in-row seed spacing, even on tight turns, or ground drive with a contact drive wheel.



### HITCH CHOICES

Four choices of hitches are offered, including Cat. 2/3 crossbar drawbar, cast single strap, or regular single strap.



### 5000 SERIES AIR-PRO® METER

Offers the highest level of singulation on the market today, and achieves uniform spacing by "dead-dropping" the seed into the trench.

## OPTIONS (see website for complete list of features & options)



MARKERS



GAUGE WHEEL SCRAPERS



LIQUID OR DRY FERTILIZER



COULTERS & ROW CLEANERS



ISO-6 CONTROL SYSTEM