

NO-TILL SEEDER

The NTS26 No-Till Seeder, available in 7', 9', and 11' widths, makes quick work of renovating pastures, reclaiming rightsof-way, and planting food plots. Designed with ease of use in mind, the NTS26 Series Seeder comes with a variety of builtin features. Metering is ground-driven by the rear packerroller. Any of the seed boxes can easily be disengaged with simple lockout pins on each drive sprocket, or all the boxes can be locked out with one pin on the main sprocket.



NO-TILL SEEDER MODELS

No-Fill Seeder	Working Width	Transport Width	Transport Height	Engine H.P. Required	Weight
NTS2607	7' 2"	8' 1"	N/A	40-60	1,878-2,800
NTS2609	8' 4"	9' 3"	N/A	50-85	2,090-3,123
NTS2611	10' 9"	11' 7"	N/A	60-110	2,650-3,800

See www.greatplainsag.com for complete specifications. Specifications are subject to change without prior notification Images may not depict current or standard production models.



NTS2607 NTS2609

NTS2611

FEATURES & BENEFITS

METERING COMPONENTS

All three boxes utilize the same proven metering components found in all Great Plains seeding equipment. These three metering systems allow the No-Till Seeder to plant a wide variety of crops, from the smallest clovers to the fluffiest native grasses.



Main Box



Small Seeds Box



Native Grass Box (optional)



ADDITIONAL STANDARD FEATURES

- Straight rear roller: 11-3/8" diameter, notched, cast gray iron rings
- Dual front spiked rollers are adjustable up to 18° •
- Roller spike: 5/8" x 2", heat-treated steel, replaceable •
- Formed plate A-frame •
- 3" x 4" tube frame
- Heavy-duty lid w/ seed splash quard
- Seed box lockouts
- Anti-reverse clutch to prevent seed cup damage
- Wide range of calibration settings
- Wind-quarded seed drop
- Lift hooks
- LED safety lighting



CHOOSE 3-POINT OR PULL-TYPE The unique design allows the machine to be converted from a 3-point to a pulltype by adding a tongue and hydraulic gauge wheels.



ADJUSTABLE FRONT ROLLER Manually-adjustable front roller controls how aggressively soil is prepped for the seedbed. Run with minimum soil disturbance or set the angle for more aggressive tillage.



3-SPEED TRANSMISSION

A simple and easy repositioning of the drive gear allows for three drive speeds (high, low, and low reduction) and one neutral position.



GROUND-DRIVE ROLLER

The rear packer (roller) utilizes spikes to drive the metering unit of the smallest seeds. while firming seed in place.



SMALL SEEDS BOX Provides accurate metering

OPTIONS (see website for complete list of features & options)







PULL-TYPE OPTION

DIGITAL ACREMETER