

**GRAVELY**

# PRO TURN MACH ONE

**WHERE OVERGROWN GRASS BECOMES JUST GRASS.**

Whether it's thick wet conditions, overgrown properties, or stalky grasses in its path, the Mach One easily cuts it down to size. Its High-Volume Output deck with tunnel chamber directs clippings away from the blades after they're cut to keep them from bogging down.

**5YR**  
FIVE YEAR OR 1250 HOUR  
WARRANTY



## 60"

**MODEL - 992515**

31 HP /Kawasaki® FX921V Engine

**MODEL - 992519**

38.5 HP / Kawasaki® FX1000V EFI Engine


**HIGH-VOLUME OUTPUT (HVO) DECK** The HVO deck provides increased depth from trim side to discharge side so it can process greater material volume.

**TUNNEL CHAMBER** An advanced cutting chamber is formed by setting the blades back four inches from the front of the deck for less clumping and even grass dispersion.

**INTEGRATED SEAT ISOLATORS** Bumps and engine vibration are smoothed out thanks to vibration-absorbing dampers.



HIGH-VOLUME OUTPUT (HVO) DECK



TUNNEL CHAMBER



INTEGRATED SEAT ISOLATORS

# PRO-TURN<sup>®</sup> MACH ONE



See your professional Gravely<sup>®</sup> dealer for complete warranty details.

	60	60
<b>MODEL NUMBER</b>	<b>992515</b>	<b>992519</b>
<b>ENGINE</b>	KAWASAKI <sup>®</sup> FX921V	KAWASAKI <sup>®</sup> FX1000V EFI
<b>HORSEPOWER</b>	31 HP	38.5 HP
<b>DISPLACEMENT</b>	999 CC	999 CC
<b>DRIVE SYSTEM</b>	HYDRO-GEAR <sup>®</sup> ZT-5400 TRANSAXLES	
<b>FUEL CAPACITY</b>	13.4 GAL	
<b>GROUND SPEED (APPROX) (Forward/Reverse)</b>	13 MPH / 6 MPH	
<b>DECK</b>		
<b>DECK MATERIAL</b>	7 GA. STEEL W/ .25 IN. SPINDLE REINFORCEMENT	
<b>DECK CONSTRUCTION</b>	WELDED	
<b>NUMBER OF SPINDLES</b>	3	
<b>BLADE TIP SPEED (FPM)</b>	18,633	
<b>SPINDLE HOUSING MATERIAL</b>	FORGED ALUMINUM	
<b>SPINDLE BEARINGS</b>	BALL BEARING	
<b>DECK ENGAGEMENT</b>	OGURA <sup>®</sup> GT3.5 ELECTRIC CLUTCH	
<b>CUTTING WIDTH</b>	60 IN	
<b>CUTTING HEIGHTS</b>	1.5 IN - 5.5 IN	
<b>CUTTING POSITIONS</b>	19	
<b>WHEELS</b>		
<b>FRONT AXLE</b>	FIXED, GREASEABLE CASTER FORK TUBES	
<b>FRONT</b>	SMOOTH 15 X 6-6 W/ GREASEABLE TAPERED ROLLER BEARINGS	
<b>REAR</b>	TURF 24 X 12-12	
<b>FEATURES</b>		
<b>SEAT</b>	HIGH BACK COMFORT W/ FULL SUSPENSION AND PADDED ARMRESTS	
<b>FOLDABLE ROPS</b>	STANDARD	
<b>MACHINE</b>		
<b>WEIGHT</b>	1486 LBS	1502 LBS
<b>LENGTH</b>	86.2 IN	
<b>WIDTH (W/ CHUTE UP/DOWN)</b>	61 IN / 74.6 IN	
<b>HEIGHT (W/ ROPS EXT/DOWN)</b>	76 IN / 47.75 IN	
<b>GROUND CLEARANCE (UNDER REAR WHEELS)</b>	4.5 IN	
<b>WARRANTY</b>		
<b>UNIT</b>	5 YEAR / 1250 HOUR COMMERCIAL / NO HOUR LIMIT FIRST TWO YEARS - SEE YOUR PROFESSIONAL GRAVELY <sup>®</sup> DEALER FOR COMPLETE WARRANTY DETAILS	
<b>DECK SHELL &amp; FRAME</b>	LIMITED LIFETIME	

## ATTACHMENTS & ACCESSORIES

TRAILER HITCH KIT  
 HEADLIGHT KIT  
 SUNSHADE KIT  
 REAR TWEEL KIT  
 SEMI-PNEUMATIC FRONT TIRE KIT  
 WHEEL COVER KIT  
 AIR RIDE SEAT KIT  
 RADIAL DRIVE CONVERSION KIT  
 TUNE UP KIT

# GRAVELY<sup>®</sup>

GRAVELY.COM

AN ARIENS|CO BRAND

© Copyright 2022 AriensCo. All rights reserved. Registered trademark and <sup>™</sup> trademark of Ariens Company. Briggs & Stratton<sup>®</sup>, Kohler<sup>®</sup>, Kawasaki<sup>®</sup>, Subaru<sup>®</sup>, Yamaha<sup>®</sup> and Hydro-Gear<sup>®</sup> are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit [gravely.com](http://gravely.com) for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.