



S N O W P L O W

QuickCube Spreader

APPLICATIONS: SKID STEER



SPECIFICATIONS

QuickCube

Cube Capacity	1/2 Cubic yard (0.38 cubic m)
Cube Length	38" (97 cm)
Cube Height	38" (97 cm)
Cube Width	46" (117 cm)
Cube Weight (Empty)	100 lb (45 kg)
Cube Construction	Gray HDPE (High-density polyethylene)
Cover Construction	Gray HDPE (High-density polyethylene)
Spreader Overall Height	54" (137 cm)
Spreader Overall Width	47.5" (121 cm)
Spreader Weight	420 lbs (190 kg)
Spreader Construction	High Strength Steel
Fork Construction	AR400 & High Strength Steel
Spreading Width	2 ft-40ft (0.6 m - 12.2 m)
Max Feed Rate	2 cubic ft per min (.057 cubic meters per min)
Attachment Style	Standard Skid Steer Attachment - SAE J2513
Hydraulic Motor	3010 in-lb Torque MAX, 600 RPM MAX
Flow Control Block	Standard
Control	Skid Steer Auxiliary Controls
Hydraulic Coupler Type/Size	Standard - 10 ORB Flush Face Quick Couplings
Hydraulic Hose Type/Size	-08 and -10 JIC & ORB, Parker 387, ISO 18752-DC
Material Conveying Method	Stainless Steel Auger
Adjustable Deflector	Standard
Spinner	14.25" Diameter - Stainless Steel

BOSS Products, a division of The Toro Company, reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein.

©2017 BOSS Products/The Toro Company. All rights reserved. Patents: www.ttcopats.com