

X-SERIES MODELS FOR MID TO FULL-SIZE EXCAVATORS & LOADER BACKHOES



The X-series is ideal for land clearing and maintenance of trails, river banks, hill sides, fire breaks, and around fences. The Brush Wolf performance-driven design will make the most of your equipment.

It starts with the combination of pairing the correct hydraulic motor and right angle gearbox to achieve the highest torque available from your equipment while maintaining a proven tip speed ideal for brush cutting applications. Power, performance and reliability are built-in. We offer over eight models to choose from. It is important to know the flow and pressure available at the "stick" or end of the boom, as well as your machines weight restrictions. You'll find the right model to make the most of what your excavator or loader backhoe has to offer with options available in: low flow, standard or high flow.

You can count on the X-Series to handle your workload now and in the future. Cutter and custom hanger priced separately.

SPECIFICATIONS	4800X LF Low Flow	4800X Standard	4800X HF* High Flow	6000X Standard	6000X HF* High Flow	6600X Standard	6600X HF* High Flow
Cutting Width:	48.000	48.000	48.000	60.000	60.000	66.000	66.000
Overall Width:	51.130	51.130	51.130	63.250	63.250	69.250	69.250
Overall Length:	62.800	62.800	62.800	74.800	74.800	80.800	80.800
Blade Carrier Type:	1.000 Steel Disc High Strength Steel			1.000 Bar Welded to .313 Spun Formed Pan High Strength Steel			
Blades:	(2) Blades at .500 x 4.000 (High Strength, Updraft)						
Blade Rotation:	Counter Clockwise						
Drive Protection:	GRD-2 Bolt (Shear Bolt)						
Motor/Gearbox Coupler:	Machined Steel						
Motor Protection:	Pressure Reliefs						
Deck Thickness:	.188 One Piece of Formed Steel			.250 One Piece of Formed Steel			
Hydraulic Hose with Protective Wrap**:	90.000						
Flat Face Coupling**:	STANDARD WITH BRUSH WOLF						
Gearbox Seal Guard:							
Req. Gallons Per Minute:	14 - 23	24 - 34	35 - 40	24 - 34	35 - 40	24 - 34	35 - 40
PSI MIN/MAX:	3000/3500	3000/3500	3000/4100	3000/3500	3000/4100	3000/3500	3000/4100
Cutting Capacity Max.:	3"	4"	5"	4"	5"	4"	5"
Weight***:	880 lbs.	880 lbs.	968 lbs.	1,332 lbs.	1,384 lbs.	1,434 lbs.	1,486 lbs.

*All high flow models include a case drain to relieve excess pressure build-up and protect hydraulic motor life. **Custom sizes and lengths available upon request.

***Weight of the cutter does not include the hanger brackets. Safety information: always operate skid steer according to manufacturers recommendation.

Operator of excavator should be behind shatter-proof glass.

X-Series Performance-Driven Standards

- Deck is formed from one piece of steel for long-lasting durability.
- Gearbox and motor assembled on a 1/2" steel plate and then welded to the deck to ensure proper alignment.
- Welded collar on bottom deck helps prevent damage to gearbox seal.
- Shear bolt protected at motor coupler.
- Balanced stump jumper to prevent vibration.
- Tempered blades with updraft for lift and mulching action.
- Relief valves protect your motor from pressure spikes and aid in faster shut-down time.
- Hoses and couplers are standard with all models - ready to go upon delivery.
- Galvanized 5/16" safety chain links on front and rear to protect against flying debris. Front chains are replaceable.
- For added safety, a reinforced plate "pilot guard" is welded to the underside of the cutter deck.
- All high flow models include a case drain to relieve excess pressure build-up and protect hydraulic motor life.
- Each Brush Wolf has a custom-made bolt-on hanger to fit your excavator. The cutter and custom hanger are priced separately.
- **Three year warranty on the structural steel on compact to full size models.**



The 4200X is designed for excavators and backhoes in the mini or compact category. It has the same reliability and durability of all Brush Wolf Models. The versatile 4800 LF Model can be attached to either compact or full-size excavators dependent upon your equipments weight restrictions and auxiliary hydraulic flow requirements.

The long-lasting high-tempered steel blades cut through up to 3" trees and branches.



Close-up view of the custom-made excavator hanger

SPECIFICATIONS	4200X
Cutting Width:	42.000
Overall Width:	45.130
Overall Length:	56.800
Blade Carrier Type:	1.000 Disc High Strength Steel
Blades:	(2) .500 x 4.000 (High Strength, Updraft)
Blade Rotation:	Counter Clockwise
Drive Protection:	GRD-2 Bolt (Shear Bolt)
Motor / Gearbox Coupler:	Machined Steel
Motor Protection:	Pressure Reliefs
Deck Thickness:	10 Gauge One Piece of Formed Steel
Hydraulic Hose with Protective Wrap*:	90.000
Flat Face Coupling:	STANDARD
Gearbox Seal Guard:	
Cutting Capacity Max.:	3"
Required GPM:	14 - 23
PSI MIN/MAX:	3000/3500
Weight**:	690 lbs.

*Custom sizes and lengths available upon request.

Weight of the cutter does not include the hanger brackets. **Operator of excavator should be behind shatter-proof glass.