

MODELS FOR UNIQUE APPLICATIONS - 9000 SERIES



The 9000 High Flow has two motors and a four (4) blade off-set cutting system to ensure full coverage of the massive 7.5 feet. You will quickly tackle your project with this powerhouse. The combination of long-lasting high strength tempered steel blades, one piece formed 1/4" heavy-duty steel, and the balanced spun formed pan will provide the strength and stability to move through tough overgrowth. Front and rear chains aid in mulching and containment of debris. The front chains are replaceable. The 9000 High Flow will mow down up to 6" brush. All high flow models include a case drain to relieve excess pressure build-up and protect hydraulic motor life. **Three year warranty on the structural steel.**

SPECIFICATIONS	9000 Standard	9000 High Flow*
Cutting Width:	90.000	90.000
Overall Width:	93.250	93.250
Overall Length:	78.375	78.375
Blade Carrier Type:	(2) 1.000 Disc High Strength Steel	
Blades:	(4) .500 x 4.000 (High Strength, Updraft)	
Blade Rotation:	Off Set - Counter Clockwise	
Drive Protection:	GRD-2 Bolt (Shear Bolt)	
Motor/Gearbox Coupler:	Machined Steel	
Motor Protection:	Pressure Reliefs	Pressure Reliefs, Case Drain
Deck Thickness:	.250 One Piece of Formed Steel	
Hydraulic Hose with Protective Wrap**:	90.000	
Flat Face Coupling**:	STANDARD	
Gearbox Seal Guard:		
Cutting Capacity Max.:	4"	6"
Required GPM:	21 - 25	26 - 40
PSI MIN/MAX:	3000/3500	3000/4100
Weight of Cutter:	1,790 lbs.	1,812 lbs.

*All high flow models include a case drain to relieve excess pressure build-up and protect hydraulic motor life. Safety information: always operate skid steer according to manufacturers recommendation.

**Custom sizes and lengths available upon request.

Operator of skid steer should be behind shatter-proof glass.

