

# JBS TRUCK MOUNT MANURE SPREADER



The JBS Truck Mount Manure Spreader increases your ability to travel on public roads. The Truck Mount Manure Spreader is available from 18 to 26 feet with 4 foot high walls, in both Narrow Body 6 feet 6 inches and Wide Body 7 feet 4 inches for more volume. The Wide Body Truck Mount can easily be converted for silage. The Truck Mount Manure Spreader comes standard with a Vertimax attachment with dynamically balanced twin vertical augers. JBS Truck Mount Manure Spreaders have a superior direct drive to drive the beaters. There are two different hydraulic systems available, basic economic controls or hydraulic piston pump with GPS feed rate controls. The Truck Mount can handle all types of manure; a hydraulic guillotine gate allows you to control the flow.

- Auger protection via Shear bolt
- Reversible cutters
- Spinner cowling
- Steel Idler sprocket bronze bushings
- 2 3/16 inches diameter rear drive shaft
- Long lasting composite floor shaft bearings
- One piece 1/2 " UHMW flooring
- WR78 floor chain
- Narrow Body Truck Mount comes standard with Helico Gearbox

## OPTIONS

- Hurricane attachment
- Wall extensions
- Paint color and decal packages
- Narrow or Wide Body
- Fenders with mud flaps
- Electric/hydraulic controls
- Angled or straight bulkhead
- Fold away lights



# JBS TRUCK MOUNT MANURE SPREADER



## JBS NARROW BODY TRUCK MOUNT MANURE SPREADER SPECS

MODEL:	VMT1848	VMT2048	VMT2248	VMT2448	VMT2648
LENGTH	18 ft	20 ft	22 ft	24 ft	26 ft
LEVEL CAPACITY	468 ft <sup>3</sup>	520 ft <sup>3</sup>	572 ft <sup>3</sup>	624 ft <sup>3</sup>	676 ft <sup>3</sup>
HEAPED CAPACITY	585 ft <sup>3</sup>	650 ft <sup>3</sup>	715 ft <sup>3</sup>	780 ft <sup>3</sup>	845 ft <sup>3</sup>
FLOOR DRIVE	Single	Single	Dual	Dual	Dual

## JBS NARROW BODY TRUCK MOUNT MANURE SPREADER SPECS

MODEL:	VMWBT1848	VMWBT2048	VMWBT2248	VMWBT2448	VMWBT2648
LENGTH	18 ft	20 ft	22 ft	24 ft	26 ft
LEVEL CAPACITY	533 ft <sup>3</sup>	592 ft <sup>3</sup>	651 ft <sup>3</sup>	710 ft <sup>3</sup>	769 ft <sup>3</sup>
HEAPED CAPACITY	666 ft <sup>3</sup>	740 ft <sup>3</sup>	814 ft <sup>3</sup>	888 ft <sup>3</sup>	962 ft <sup>3</sup>
FLOOR DRIVE	Dual	Dual	Dual	Dual	Dual

This machine is designed for off-road agricultural use only. For other applications, please contact J. Bond & Sons Ltd. J. Bond & Sons Ltd. reserves the right to improve or modify our product without notice or obligation.

**AUTHORIZED DEALER**