

Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0 Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122 husky@huskyfarm.ca www.huskyfarm.ca



Special Order Only

HUSKY 18000 ELITE

Special Order Only

5000 US Gal., 4000 CDN Gal., 18000 Litres

28L x 26, 12 Ply Tires Compaction 3744 sq. in. on ground

Tire type Turf type, knobby tread

Overall height 120" Overall width 163" 100" Tank width 78" Tank height Tank length 15 ft

Tank ends Flanged and reinforced Tank shell thickness 3/16" high strength steel

Number of baffles 2 full baffles

Hitch Single or optional double hitch

Tongue jack 8000 lbs

Axle weight (less tires) 3252 lbs, 1475 kg Axle capacity 80,000 lbs, 36288 kg Axle warranty 5 year (non commercial) 4 1/4" stress proof HT SR Axle spindle size & material

10 bolt, 11.25 " bolt circle, 8 5/8" pilot hole, greaseable Hub bolt pattern







Standard Features

Bearings Tapered roller

Seals Double lip grease purge able

PTO Constant velocity shear protected 1 3/8 6 T,

1 3/8 21T, 1 3/4 20T Size of discharge 6"

Spreading pattern Up to 60 ft, 18 m

Discharge height 106", 2692 mm optional 4 ft

Unloading speed 6" discharge Up to 2400 gallon

per minute adjustable

Painting preparation Steamed with phosphate

Paint primed Epoxy

Paint finish coat Urethane

Inside coating Aluminized epoxy

Axle warranty 5 year unconditional

Light kit (brake & tail) Standard

Unloading pump 4 blade fan type

Draw bar weight Adjustable

Walking tandem Axle

Seams welded solid inside

U shape, 1/4" Sill

6 square ft Padding to tank contact

4"x 8" boxed tubing 1/4" material on tongue

73" Tongue



Options For Your Husky Tank

8" Discharge Unloading speed Up to 3600 gallon per minute adjustable

Hydraulic drive

Butterfly Lid

Clean Out

Camels Hump

Pipe Down the back

Sight Gage

Swing Away Fan

Slide Lid

Square Man Hole

In tank Agitation

Valves

1000 RPM Unload

Low Spread

Single Hitch