

Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0
Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122
husky@huskyfarm.ca www.huskyfarm.ca



18,000 L SLIM LINE

5000 US Gal., 4000 CDN Gal., 28L x 26, 12 Ply

Turf type, knobby tread 24 PSI 3744 (square inches on ground)

116" High 126" overall width

Tank 101" wide 75" high 18 ft long

Tank ends flanged and reinforced 3/16" high strength steel

Tank shell thickness 3/16" high strength steel

2 full baffles 3/16" high strength steel

Single or double hitch with 8000 lbs tongue jack

6" discharge Up to 2400 gallon per minute adjustable

1000, 540 RPM Fan with hi efficiency blades

Timken taper bearings, grease filled chamber double seals, purgeable

Walking tandem axle 5 year warranty (non commercial)

4 1/4" stress proof HT SR spindle 16,000 LBS

Axle weighs 3252 lbs (1475 kg) (without tires)

80,000 lbs (36,288 kg) capacity

10 bolt Hub greaseable 11.25" bolt circle 8 5/8" pilot hole greaseable

WEIGHT

Empty 13,082 lbs (5,936 kg) Loaded 54,732 lbs. (24,826 kg)

Options For Your Husky Tank

8" Discharge Unloading speed Up to 3600 gallon

per minute adjustable

Hydraulic drive

Butterfly Lid

Clean Out

Camels Hump

Pipe Down the back

Sight Gage

Swing Away Fan

Slide Lid

Square Man Hole

Cut Outs

High Speed Tires

Steering

In tank Agitation

Valves

1000 RPM Unload

Low Spread

Single Hitch







Standard Features

Bearings Tapered roller Seals Double lip grease purge able PTO Constant velocity shear protected 1 3/8 6 T, 1 3/8 21T, 1 3/4 20T

Size of discharge 6"

Spreading pattern Up to 60 ft, 18 m Discharge height 106", 2692 mm optional 4 ft

Unloading speed 6" discharge Up to 2400 gallon per minute adjustable

Painting preparation Steamed with phosphate Paint primed Epoxy

Paint finish coat Urethane

Inside coating Aluminized epoxy

Axle warranty 5 year unconditional

Light kit (brake & tail) Standard Unloading pump 4 blade fan type

Draw bar weight Adjustable

Walking tandem Axle

Seams welded solid inside

U shape, 1/4" Sill

6 square ft Padding to tank contact

4"x 8" boxed tubing 1/4" material on tongue

73" Tongue



