

## Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0 Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122 husky@huskyfarm.ca www.huskyfarm.ca



## 18000L Vacuum

5000 US Gal., 4000 CDN Gal., 18000 Litres



28L x 26, 12 Ply

Compaction 3744 sq. in. on ground

Tire pressure 24 lbs

Tires

Tire type Turf type, knobby tread

Overall height 120" 163" Overall width Tank width 100" Tank height 78" Tank length 15 ft Number of baffles 2 full baffles Inside coating Aluminized epoxy

Single or optional double hitch Hitch

Tongue jack 8000 lbs

Axle weight (less tires) 3252 lbs, 1475 kg 80,000 lbs, 36288 kg Axle capacity Axle warranty 5 year (non commercial) Axle spindle size & material 4 1/4" stress proof HT SR

10 bolt, 11.25 " bolt circle, 8 5/8" pilot hole, greaseable Hub bolt pattern

**Empty** 13,082 lbs (5,936 kg) Loaded 54,732 lbs (24,826 kg) Primary and secondary moisture trap with 6" stainless ball

1/4" (6.35 mm) tank shell high strength steel

1/4" Tank ends flanged and dished Full Baffle welded inside and out Sight gauge standard front drivers side Walking tandem axle 5 year warranty 24" rear access hatch, 6" hydraulic discharge

6" manual side valve

15 feet 6" suction hose with Bauer ends 3" (75 MM) air intake and outlet lines

10 Year rust out warranty

High speed vacuum pumps air cooled High heat vanes / air cooled / 540/ 1000 Options For Your Husky Tank

Hydraulic drive

Valves

1000 RPM Unload Single Hitch Hydraulic lid

Vacuum pumps 6 sizes to

choose from

30 " Domed manhole



## **Standard Features**

PTO Constant velocity shear protected 1 3/8 6

T, 1 3/8 21T, 1 3/4 20T Size of discharge 6"

Painting preparation Steamed with phosphate

Paint primed Epoxy Paint finish coat Urethane Inside coating Aluminized epoxy Axle warranty 5 year unconditional Light kit (brake & tail) Standard Draw bar weight Adjustable Walking tandem Axle

Seams welded solid inside U shape, 1/4" Sill

6 square ft Padding to tank contact

4"x 8" boxed tubing 1/4" material on tongue

73" Tongue