

7400 US Gal., 6000 CDN Gal., 28000 Litres

30.5L x 32, 12 Ply

Compaction Tire pressure Tire type Overall height Overall width Tank width Tank height Tank length Tank ends Tank shell thickness Number of baffles Tongue jack Axle weight (less tires) Axle capacity Axle warranty Axle spindle size & material Hub bolt pattern Empty Loaded

Turf type, knobby tread 125" 163" 100" 78" 23 ft Flanged and reinforced 1/4" 2 full baffles 8000 lbs 4432 lbs 100,000 lbs 5 year (non commercial) 5 1/2" stress proof slid in 6 1/2" sleeve 10 bolt, 13.19" bolt circle, hub greaseable 18,834 lbs (8560 kg) 80,476 lbs (36,580 kg)

4508 sq. in. on ground

24 lbs

Options For Your Husky Tank 8" Discharge Unloading speed Up to 3600 gallon per minute adjustable Hydraulic drive Butterfly Lid Clean Out Camels Hump Pipe Down the back Sight Gage Swing Away Fan Slide Lid In tank Agitation Valves 1000 RPM Unload Low Spread Single Hitch



Standard Features

Bearings Tapered roller Seals Double lip grease purge able PTO Constant velocity shear protected 1 3/8 6 T, 1 3/8 21T, 1 3/4 20T Size of discharge 6" Spreading pattern Up to 60 ft, 18 m Discharge height 106", 2692 mm optional 4 ft Unloading speed 6" discharge Up to 2400 gallon per minute adjustable Painting preparation Steamed with phosphate Paint primed Epoxy Paint finish coat Urethane Inside coating Aluminized epoxy Axle warranty 5 year unconditional Light kit (brake & tail) Standard Unloading pump 4 blade fan type Draw bar weight Adjustable Walking tandem Axle Seams welded solid inside U shape, 1/4" Sill 11.5 square ft Padding to tank contact 4"x 8" boxed tubing 1/4" material on tongue 73" Tongue

