

## Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0 Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122 husky@huskyfarm.ca www.huskyfarm.ca



## 28000L Vacuum

7400 US Gal., 6000 CDN Gal., 28000 Litres 30.5L x 32, 12 Plv

Compaction 4508 sq. in. on ground

Tire pressure 24 lbs

Tire type Turf type, knobby tread

Overall height 125" Overall width 163" 100" Tank width Tank height 78" Tank length 23 ft

Number of baffles 2 full baffles

Single or optional double hitch Hitch

Tongue jack 8000 lbs Axle weight (less tires) 4432 lbs Axle capacity 100,000 lbs

Axle spindle size & material 5 1/2" stress proof slid in 6 1/2" sleeve 10 bolt, 13.19" bolt circle, hub greaseable Hub bolt pattern

**Empty** 18,834 lbs (8560 kg)

Loaded 80,476 lbs (36,580 kg) 1/4" (6.35 mm) tank shell high strength steel

1/4" Tank ends flanged and dished Full Baffle welded inside and out Sight gauge standard front drivers side 24" rear access hatch, 6" hydraulic discharge

6" manual side valve

15 feet 6" suction hose with Bauer ends

Primary and secondary moisture trap with 6" stainless ball

3" (75 MM) air intake and outlet lines

10 Year rust out warranty

High speed vacuum pumps air cooled High heat vanes / air cooled / 540/1000

Options For Your Husky Tank

Hydraulic drive Clean Out Sight Gage Swing Away Fan **High Speed Tires** In tank Agitation

Valves

1000 RPM Unload Single Hitch Hydraulic lid

Vacuum pumps 6 sizes to choose from

30 " Domed manhole



## **Standard Features**

Bearings Tapered roller Seals Double lip grease purge able

PTO Constant velocity shear protected 1 3/8 6

T, 1 3/8 21T, 1 3/4 20T Size of discharge 6"

Spreading pattern Up to 60 ft, 18 m

Discharge height 106", 2692 mm optional 4 ft Unloading speed 6" discharge Up to 2400

gallon per minute adjustable

Painting preparation Steamed with phosphate

Paint primed Epoxy

Paint finish coat Urethane

Inside coating Aluminized epoxy

Axle warranty 5 year unconditional

Light kit (brake & tail) Standard

Unloading pump 4 blade fan type

Draw bar weight Adjustable

Walking tandem Axle

Seams welded solid inside

U shape, 1/4" Sill

11.5 square ft Padding to tank contact 4"x 8" boxed tubing 1/4" material on tongue

73" Tongue