

Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0 Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122 husky@huskyfarm.ca www.huskyfarm.ca



30500L Tri Axle



30.5L x 32, 12 Ply, Optional 35.5 x 32

Compaction 4508 sq. in. on ground

Tire pressure 26/30 lbs

Tire type Turf type, knobby tread Tank ends Flanged and reinforced 1/4" high strength steel Tank shell thickness

2 full baffles Number of baffles Inside coating Aluminized epoxy

Light kit (brake & tail) Standard Seams welded solid inside Yes

Sill style & thickness U shape, 1/2" material, 3/4" over axle

Padding - sills to tank contact 12 square ft

Tongue type and thickness 4" x 8" rectangular tubing 3/8" material

Single or optional double hitch Hitch

8000 lbs Tongue jack

Unloading pump Fan type with high efficiency blades

1000, optional 540 RPM **RPM**

Hydraulic drive **Optional**

Bearings Timken taper, grease filled chamber

Double seals, purgeable Seals

Constant velocity, shear protected 1 3/8 6T, 1 3/8 21T, 1 3/4 20T PTO

Hydraulic drive Optional

Size of discharge 6

Unloading speed 6" discharge Up to 2400 gallon per minute adjustable

Spreading pattern Up to 60 ft Discharge height 135" optional 4 ft Walking tandem Axle type 4432 lbs, 2009 kg Axle weight (less tires)

Axle capacity


Axle warranty 5 year (non commercial)

Hub bolt pattern 10 bolt, 13.19" bolt circle, 11 1/16 pilot hole, hub greaseable

Steamed with phosphate Paint primerAluminized epoxy acid resistant Painting preparation

Paint finish coat Urethane acid resistant

Empty 24,0004 lbs Loaded 94,000 lbs



Overall Length 12356mm 486" 40.5ft

(With Inside Agitation) Tank Width 2565mm 101" Tank Height 1920mm 75.5" Tank Length 9144mm 360" 36ft

Number Of Baffles 4

Sill Out Side Dimension 1372mm 54"

Tongue Length 1905mm 75"



Options For Your Husky Tank 8" Discharge Unloading speed Up to 3600 gallon per minute

adjustable Hydraulic drive Butterfly Lid Clean Out Camels Hump Pipe Down the back

Sight Gage In tank Agitation

Valves

1000 RPM Unload Low Spread Single Hitch

