



Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0
Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122
husky@huskyfarm.ca www.huskyfarm.ca



7000L Galvanized

1800 US Gal., 1500 CDN Gal., 7000 Litres

	16.5L x 16.1, 10 Ply
Compaction	1208 sq. in. on ground
Tire pressure	35 PSI
Tire type	Rib implement type
Overall height	94 " (2387 mm)
Overall width	97.75" (2482 mm)
Tank width	60" (2184 mm)
Tank height	60" (2184 mm)
Tank length	12 ft (3.66 m)
Tank ends	Flanged
Tank shell thickness	3/16" (4.5 mm)
Number of baffles	1
Hitch	Single or double, height adjustable
Tongue jack	5000 lbs
Axle capacity	32000 lbs
Axle spindle size & material type	2 3/4" SPS Stress proof material
Hub bolt pattern	8 bolt, 8" bolt circle, 6" pilot hole
Axle width hub flange to hub flange	Straight axle 82.25"
Empty	4,550 lbs (2,063 kg)
Loaded	17,045 lbs (7,731 kg)

Standard Features

Bearings Tapered roller
 Seals Double lip grease purge able
 PTO Constant velocity shear protected 1 3/8 6 T,
 1 3/8 21T, 1 3/4 20T
 Size of discharge 6"
 Spreading pattern Up to 60 ft, 18 m
 Discharge height 106", 2692 mm optional 4 ft
 Unloading speed 6" discharge Up to 2400 gallon
 per minute adjustable
 Hot Dip Galvanized
 Axle warranty 5 year unconditional
 Light kit (brake & tail) Standard
 Unloading pump 4 blade fan type
 RPM 540
 Draw bar weight Adjustable
 Walking tandem Axle
 Seams welded solid inside
 U shape, 1/4" Sill
 6 square ft Padding to tank contact
 55 inch Tongue
 4"x 8" boxed tubing 3/16" material on tongue

Options For Your Husky Tank

Hydraulic drive
 Butterfly Lid
 Clean Out
 Camels Hump
 Pipe Down the back
 Sight Gage
 Swing Away Fan
 Slide Lid
 Square Man Hole
 In tank Agitation
 Valves
 1000 RPM Unload
 Low Spread
 Single Hitch