

CORROSION PROOF • ECONOMICAL • DURABLE

Ideal for all Agricultural applications.



These durable ceiling inlets are rotational moulded with high impact polyethylene. They are designed to offer efficient airflow economically with minimum maintenance. The polyethylene is easy to clean with a pressure washer.

FEATURES

- Single sided Canarm ceiling inlet.
- 1500 cfm
- Insulated door - Polyurethane injected.
- Available in mechanical and counter balanced.
- CAI-SM – single mechanical
- CAI-SCB – single counter balanced
- Inside of the lid is scooped to encourage air to hug the ceiling as long as possible.
- Features alignment boss for back to back installation.
- Rugged, pressure washer safe.

AVAILABLE INLET STYLES

- Mechanically operated (type "SM") with an actuator
- Energy free models (type "SCB") that open with static pressure and close with adjustable counter balance weight

SPECIFICATIONS

Model	Type	CFM @ 750 FPM	Frame Size
CAI-SM	Mechanical - Single	1500 CFM	22 1/2" x 18 1/4"
CAI-SCB	Counter Balanced - Single	1500 CFM	22 1/2" x 18 1/4"
CAI-SM X 2	Mechanical - Double (Back to Back)	3000 CFM	22 1/2" x 36 1/2"