

## Keep your herd clean with the push of a button!

<sup>Ințelli</sup>Cable

**Pro II** 

# Automatically clean on a precise schedule – even while you sleep!

- Advanced SmartSense<sup>®</sup> learning system constantly adjusts to weather, bedding, and manure changes while recalculating the amount of energy required to clean.
- Energy-efficient drive system!
- Drive unit design includes technology for precise scraper automation!
- Scrapers designed for easy removal.
- Easily installs in existing or new barns!
- Low maintenance!

### Let Patz handle your manure so you don't have to!

For concrete alleys or rubber flooring!





IntelliCable<sup>-</sup>

Pro III

IntelliCable®

Pro I

Programmable BUMP FEATURE for superior sensitivity!

**Alley Scraper** 

# Improve your bottom line with Patz !


- 56" (1,422 mm)

IntelliCable


- IntelliCable<sup>®</sup> Pro I
  - 1-hp electric motor
  - 60:1 worm gear speed reducer
  - #80 roller chain drive
  - 29<sup>1</sup>/<sub>2</sub>" (749 mm) diameter solid drive drum - 18" (457 mm) wide
  - 1 cable over wrap switch
  - 2" (51 mm) replaceable drive drum shaft
  - External grease fittings
  - Safety interlock
  - 3/8", 7/16", & 1/2" O.D. cable
  - Sensor disc and proximity sensors

### IntelliCable® Pro III

- <sup>3</sup>/<sub>4</sub>-hp electric motor
- Efficient 376:1 planetary speed reducer
- #80 roller chain drive
- 56" (1,422 mm) diameter drive drum -181/2" (470 mm) wide
- 2 cable over wrap switches
- 3/8", 7/16", & 1/2" O.D. cable
- Safety interlocks
- External bearings with grease fittings
- Sensor disc and proximity sensors



#### **Sensor Control**



Drive unit design includes sensor disc and proximity sensors to provide the control panel with necessary information to keep track of scraper's position and direction.

#### Reduce expenses with time, labor, and energy savings. Minimize wear on tractor/skid-steer and facilities.

Clean more often.

Reduce livestock stress with guiet, emissions-free cleaning!

We run the scrapers continuously to keep the cows as clean as possible - a key factor in keeping SCC low and herd health high. -WI Dairy Farmer

High quality milk starts with cleaner, calmer cows!



### SmartSense<sup>®</sup> MasterMind Control Panel

### Provides the quality and safety features you want for your employees and family.

- Fiberglass frame with easy-to-use, quick-connect electric cables with pre-wired junction box.
- Glove-friendly, easy-to-use, 5.7" (145 mm) color HMI touch screen display.
- Large, easy-to-recognize universal language icon navigation.
- 3 operational modes: MANual, CONTinuous, and AUTOmatic (schedule up to 12 cycles per day).
- Adjustable speed control.
- "Auxiliary Relay Function" allows the operator to automatically start another machine, lights, or horns by supplying a start signal.
- Patz innovative "Learning System."
- Superior sensitivity programmable BUMP feature.
- Advanced "Patz Remote Notification" emails and/or text messages operator(s) with scraper status and service updates. Transmits updates following corrective service.
- Faults are stored in memory up to 4 weeks—even if power is cycled. Allowing service technicians to guickly troubleshoot.
- Integrated LOCK-OUT/TAG-OUT power disconnect lever.
- HARD PULL one-button feature works great for freshly bedded alleys and times of heavy or excessive manure.
- QUICK CLEAN feature cleans alley in between scheduled cleanings.
- PARK feature positions scrapers out of way when needed (designate alternate scraper location other than HOME).
- Black plastic manual box included to protect Operator's and Parts Manuals from the environment.

Save steps and labor when you control all functions of the IntelliCable® Alley Scraper at the SmartSense



Available in: 1Ø or 3Ø, 230 V power, 50/60 Hz. Higher voltage option available.




SmartSense<sup>®</sup> Control Panel features an easy-to-use, "glove-friendly", color HMI touch screen.


**FLEXIBLE PAYMENT** PLANS AVAILABLE! **ASK FOR DETAILS** 

### IntelliCable<sup>®</sup> Drive Units

**Guard** opened

for viewing.





- Efficient 376:1 planetary speed reducer
- #80 roller chain drive
- 27½" (699 mm) diameter drive drum -18<sup>1</sup>/<sub>2</sub>" (470 mm) wide
- 2 cable over wrap switches
- 3/8", 7/16", & 1/2" O.D. cable
- Safety interlocks

'36"

- External bearings with grease fittings
- Sensor disc and proximity sensors

31¼" (794 mm)

Max. Scraped Alley Length (SAL) & Max. Total Circuit Length (TCL) w/4 Scrapers	Pro I ft. (m)	<b>Pro II</b> ft. (m)	Pro III ft. (m)
SAL with 1/2" Cable	220 (67)	215 <mark>(66)</mark>	440 (134)
SAL with 7/16" Cable	255 (78)	250 (76)	510 (155)
SAL with 3/8" Cable	285 (87)	280 <mark>(85</mark> )	570 (174)
TCL with 1/2" Cable	650 <mark>(198)</mark>	850 (259)	1,760 (536)
TCL with 7/16" Cable	800 (244)	1,000 <mark>(305)</mark>	2,040 (622)
TCL with 3/8" Cable	900 (274)	1,100 <mark>(335)</mark>	2,280 (695)


Keep your livestock clean and healthy by installing the IntelliCable® Alley Scraper, a part of the



**Guard** opened for viewing.

32" (813 mm)

### **Self-Locking Ratchet System**



The self-locking ratchet system allows easy tightening of cable.

### **Customize your IntelliCable®** Alley Scraper to fit your operation!



### **Corner Wheel**

### Patz Proven Performer

#### Corner Wheel

The 16" (406 mm) diameter cast iron corner wheels feature stainless steel fasteners as standard components. Corner wheels accept 3/8", 7/16", or 1/2" cable. Phenolic with graphite sleeve bearings for longer life.

Cover removed for viewing.

#### Folding Angled Tip-Up Scraper




- Wings pivot to follow wall tightly for better cleaning.
- During the reverse movement, blades tip up and wings pivot inward.
- Heavy enough to clean better; extra steel in wear points.
- Cleans alleys with widths from 84 to 192 inches (2.1-4.9 m).
- Replacement blades and wings available for easy servicing.
- Scraper removes easily center in slot and lift off.
- Scraper can be replaced without removing sled.





### Sleds



57" (1,448 mm) sleds provide better scraper stability. 37" (940 mm) sleds are available

where a shorter sled is required.

### For Rubber Flooring



Hard nylon rollers located on sled ends and scraper arms position the scraper above the rubber covered

alleys, ensuring only rubber blades touch rubber flooring.



 Low-profile scraper wings and folding design allow easy passage for animals, tractors, and skid-steer loaders when bedding freestalls.



- Replaceable wings available for easy servicing.
- Cleans alleys with widths from 64 to 174 inches (1.6-4.4 m).

#### Versa Folding V Scraper

 Low-profile scraper wings and folding design allow easy passage for animals, tractors, and skid-steer loaders when bedding freestalls.



- Cleans alleys with widths from 64 to 174 inches (1.6-4.4 m).
- Optional choice of three economical, replaceable, bolt-on blade edges:
  - AR400 STEEL for use with sand bedding.
  - RUBBER for use with rubber mat floors.
  - URETHANE for use with rubber mat floors or concrete (where floor wear is a concern) and sand bedding. This is a great alternative material for longer wear.
- Universal scraper wings are replaceable.

### **Plastic Jacketed Cable**



Patz blue plastic jacketed galvanized steel cable is cow friendly with superior wear resistance against stretching,

fraying, sand, sawdust, and manure. Provides longer service life than steel cable.

**CAUTION:** Never operate Patz equipment without all shields and guards in place. Safety is no accident. Before operating any piece of equipment, be sure to read and understand the operator's manual. This manual should be kept with the machine at all times.

Additionally, make sure all safety shields and devices are functioning properly and are securely in place.

For some photos in this brochure, guards were removed for photographic purposes only to allow viewing of the equipment features. Before operating equipment, all guards must be in place. Because Patz continually improves and updates products, Patz reserves the right to change the construction of machines or attachments or any part thereof without incurring any obligation to make like changes on Patz machines, or attachments previously delivered. Specifications and prices subject to change without notice.

# Patz Since 1948

### Proven Performance You Can Count On! Patz Corporation

917 Business 141, POB 7 • Pound, Wisconsin 54161-0007 Ph: (920) 897-2251 • Fax: (920) 897-2142 www.patzcorp.com • info@patzcorp.com

PA-26731 Rev. 8/15 ©2013-2017 Patz Corporation Printed in U.S.A.

Watch video online Polar Vortex No Match For Patz IntelliCable<sup>®</sup>.



The name generations of farmers have entrusted with their feed and manure handling needs!



You