

MX & MX-C SERIE

Angular paddle TMR mixer
stationary or mobile

- Designed by Rovibec Agrisolutions, this TMR mixer is ideal for the producer looking for top quality mixer that can adapt from a medium to large size herds.
- This TMR mixer blade will allow you to prepare best quality recipe for your herd.
- Its smooth operation as well as the unique angular paddle design allowing recipe to mix evenly with complete, perfectly homogeneous mixture by smooth operation without breaking the fibres ; providing a healthy diet for your herd.
- The MX-C TMR mixer equipped with famous Rovibec designed knives (secured onto inner tub liner) offers cutting fibre with a sharp and even cut without breaking fibre, while performing homogenous mixing.
- Inner tub liner supplied with a high resistance grade UHMW protecting mixing tub against friction and corrosive reaction to silage.

Load and specification chart

Model	Motor		Tub capacity		Mixing capacity			Overall length ***		Overall width ***		Height		Tare weight	
	HP	pi3	m3	Kg *	pi3	m3	Kg *	ln***	mm***	ln***	mm***	ln	mm	lbs	Kg
MX 660	5	170	4.8	2040	150	4.2	1800	94	2388	92	2337	87	2210	3377	1532
MX 860	7.5	265	7.5	3180	200	5.7	2400	112	2845	92	2337	87	2210	4620	2096
MX 1060	7.5	332	9.4	3984	270	7.6	3240	135	3429	92	2337	87	2210	6050	2744
MX 880	7.5	355	10.1	4260	300	8.5	3600	112	2845	110	2794	100	2540	5225	2370
MX 1080	7.5	442	12.5	5304	385	10.9	4620	135	3429	110	2794	100	2540	6600	2994
MX 1280	10	530	15.0	6360	450	12.7	5400	157	3988	110	2794	100	2540	7700	3493
MX 1480	10	618	17.5	7416	525	14.9	6300	187	4750	110	2794	100	2540	8855	4017
MX 1680	10	707	20.0	8484	600	17.0	7200	213	5410	110	2794	100	2540	10230	4640
MX 1880	10	795	22.5	9540	675	19.1	8100	231	5867	110	2794	100	2540	11495	5214

* The tank capacity weight in kg is based on an average weight of 8.3g per ft3, or 290Kg per m3. A variation of ± 10% must be considered.
Notice, humidity will influence volume weight

** Height based on standard MX mixer

*** Options not included into present specifications.

Model	Format		Cows fed based on 2 mixings per day
	feet	metres	
MX 660	6' X 6'	1.83 x 1.83	49
MX 860	6' X 8'	1.83 x 2.44	66
MX 1060	6' X 10'	1.83 x 3.05	88
MX 880	8' X 8'	2.44 x 2.44	98
MX 1080	8' X 10'	2.44 x 3.05	126
MX 1280	8' X 12'	2.44 x 3.66	147
MX 1480	8' X 14'	2.44 x 4.27	172
MX 1680	8' X 16'	2.44 x 4.88	197
MX 1880	8' X 18'	2.44 x 5.49	221