## **2023 OUTLANDER MAX XT-P**



## PACKAGE HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-4Lok† front differential
- FOX† 1.5 PODIUM QS3† shocks
- 14 in. cast-aluminum beadlock wheels
- 26 in. ITP Terracross† radial tires
- · Heavy-duty front and rear bumpers
- · Painted plastics for premium look
- 3,500-lb (1,588 kg) winch
- · Aluminum taper-profile handlebar with full wrap handguards
- 7.6 in. wide digital display

## Iron Gray & Neo Yellow / 850 / 1000R

| ENGINES              | 850  | 1000R   |
|----------------------|--|---|
| Туре                 | 78 hp, Rotax® 854 cc<br>V-twin, liquid-cooled                            | 91 hp, Rotax® 976 cc<br>V-twin, liquid-cooled |
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) |   |
| Transmission         | CVT, P/R/N/H/L, Intelligent Engine Braking (iEB™)                        |   |
| Drive Train          | Selectable 2WD/4WD/Lock 4WD with Visco-4Lok front differential           |   |
| Power Steering       | Tri-Mode Dynamic Power Stee  | ering (DPS)                                   |
| SUSPENSIONS          |  |   |
| Front Suspension     | Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel         |   |
| Front Shocks         | FOX 1.5 PODIUM QS3   |   |
| Rear Suspension      | Torsional Trailing arm Independent (TTI)<br>9.9 in. (25.1 cm) travel     |   |
| Rear Shocks          | FOX 1.5 PODIUM QS3   |   |
| TIRES & WHEELS       |  |   |
| Front Tires          | ITP Terracross 26 x 8 x 14 in.   |   |
| Rear Tires           | ITP Terracross 26 x 10 x 14 in.  |   |
| Wheels               | 14 in. cast-aluminum beadlock  | (   |
| BRAKES               |  |   |
| Front                | Dual 214 mm disc brakes<br>with hydraulic twin-piston calipers           |   |
| Rear                 | Single 214 mm disc brake with hydraulic twin-piston calip                | per   |

| DIMENSIONS &          |                                   | l -             |
|-----------------------|-----------------------------------|-----------------|
| CAPACITIES            | 850                               | 1000R           |
| Estimated Dry Weight* | 869 (394 kg)                      | 954 lb (433 kg) |
| LxWxH                 | 94 x 48 x 53 in. (238.8 x 121.9 x | ( 135 cm)       |
| Wheelbase             | 59 in. (149.9 cm)                 |                 |
| Ground Clearance      | 11 in. (27.9 cm)                  |                 |
| Seat Height           | 34.5 in. (87.7 cm)                |                 |
| Rack Capacity         | Front: 100 lb (45 kg)/Rear: 200   | lb (90 kg)      |
| Storage Capacity      | 5.7 gal (21.4 L)                  |                 |
| Towing Capacity       | 1,650 lb (750 kg)                 |                 |
| Fuel Capacity         | 5.4 gal (20.5 L)                  |                 |

| FEATURES        |  |
|-----------------|--|
| Gauge           | 7.6 in. wide digital display                               |
| Instrumentation | DC outlet, 15-A connector                                  |
| Lighting        | LED headlights   |
| Winch           | 3,500-lb (1,588 kg) winch                                  |
| Seat            | Convertible Rack System (CRS)                              |
| Handlebar       | Aluminum taper-profile handlebar with full wrap handguards |
| Protection      | Heavy-duty front & rear bumpers<br>Mudguards               |

| WARRANTY & EXTENDED SERVICE |   |  |
|-----------------------------|---|--|
| Factory Warranty            | 6-month BRP limited warranty            |  |
| Extended Service<br>Terms   | B.E.S.T. term available up to 36 months |  |



