

MODEL	4480XD
Overall Length	42' 8" (13 m)
Usable Deck Length	34' (10.36 m)
Overall Width	13' 10" (4.2 m)
Width (Without Loading Arm)	10' 2" (3.1 m)
Transport Width	10' 2" (3.1 m)
Overall Height	15' 10" (4.8 m)
Tipping Frame Height (Raised)	15' 10" (4.8 m)
Rotate Arm Height (Lift Arm Fully Raised)	15' 7" (4.75 m)
Weight (empty)	9485 LB. (4302 KG) (APPROX.)
Hitch Weight (empty)	1950 LB. (884 KG) (APPROX.)
Hitch Weight (maximum)	7500 lb. (3402 kg) (approx.)
Tires	Eight 12.5L x 15 - Load Range F
Hubs	8 Bolt Heavy Duty
Hub Spindle / Tire Capacity	8000 lb. (3630 kg) @ 90 psi
Hydraulic Flow (closed or open center)	25 US gpm (80 lpm) @ 3000 psi
Maximum Hydraulic Pressure	3500 psi (24132.5 kPa) (241 bar)
Operating Hydraulic Pressure	3000 psi (20685 kPa) (207 bar)
Hydraulic Motors (Pusher)	Dual 22.2 cu. in.
Lift Cylinder	4" diameter x 18" stroke
Clamp Cylinder	3" diameter x 16" stroke
Rotate Cylinder	3" diameter x 16" stroke
Tilt Cylinders	3.5" diameter x 36" stroke
Electrical	12V (Internal Fuse Protection)
Maximum Load	25,000 lb. (11,300 kg)
Bale Length	8' (2.4 m)
48" x 48" (122 x 122 cm) Bales	9 Bales (single row on carrier) / 8 Bales (single row with 1/4 turn)
32" x 35" (81 x 90 cm) Bales	24 Bales (double row on carrier) / 20 Bales (double row with 1/4 turn)
36" x 48" (91 x 122 cm) Bales	18 Bales (double row on carrier) / 10 Bales (single row with 1/4 turn)