

X5HC

X5.100HC / X5.110HC




McCORMICK

Power Technology.

SPECIFICATIONS

Tractor Model		X5.100 HC	X5.110 HC
Engine			
Max. Engine HP (ISO) @ 2200 RPM	HP (kW)	95.2 / 70	102 / 75
Max. PTO HP* (ISO) @ 2200 RPM	HP (kW)	80 / 59	88 / 65
Max. Engine Torque @ 1400 RPM	lb ft (Nm)	395	430
Engine Type	FPT F36 engine Tier 5, TACR, DOC + SCRoF, 3,6L, 4 cyl 16v		
Engine Size	3.6L, 4-Cylinder		
Fuel Capacity	gal (liter)	35.6 (135)	
Drive Train			
Standard Transmission	16 x 16 Transmission with creeper - 30 km/h		
Optional Transmission	Transmission (32 x 32) with hydraulic power shuttle & 2 speed power shift		
Rear Axle	Heavy duty flanged rear axle		
Differential Lock	Front: Hydralock full locking differentials; Rear: Electrohydraulic		
4wd Front Axle	4WD Hydralock front axle with integrated brakes		
Tire Type	Radial tires standard		
Hydraulics, 3-point Hitch, PTO			
Implement Hydraulic System Type	Open center with tandem hydraulic pumps		
Hydraulic Flow Rate	gpm (lpm)	62 (32)	
Rear Remote Valves	2 Rear spool valves S/D acting		
Rear 3-point Hitch Type	3-point linkage, Cat. 2, telescopic ball ends, pin-type telescopic stabilizers. Lift capacity 9,920 lb (4,500 kg)		
Max. Rear 3-point Lift Capacity @ Hitch	lb (kg)	9,920 (4,500)	
Rear PTO	540 / 1000 rpm PTO- Hydraulic engagement, controls on rear fender		
Operator's Area			
Cab	Cab mounted on silent blocks. True flat deck. Opening front window		
Seat and Front Dash	Cab: Cloth seat, air suspension; tilt and telescopic steering wheel		
Wheelbase	in (mm)	92.7 (2,355)	
Height Over Cab with standard wheel equipment	in (mm)	112.99 (2,870)	
Overall Length with front weights	in (mm)	9,700 (4,400)	
Base Weight without ballast	lb (kg)	13,227 (6,000)	

* Manufacturer's calculated estimate