

Rite Way Rockpicker / Windrower Specifications



Rockpickers	RR250ST	RR900ST
Drive	Variable Hydraulic Drive	Variable Hydraulic Drive
Reel	2 Bat	3 Bat
Reel Chain	#80	#80
Picking Width	50" / 127 cm	60" / 152 cm
Minimum Rock Diameter	2" / 5 cm	2" / 5cm
Maximum Rock Diameter	24" x 45" / 61 cm x 114 cm	28" x 55" / 81 cm x 140 cm
Bucket Capacity	1.25 cu yd / 0.96 cu meter	3.2 cu yd / 2.4 cu meter
Reel & Bucket Control	Electric over Hydraulic	Electric over Hydraulic
Weight Capacity	3,600 lbs. / 1,650 kg	4,784 lbs. / 2,170 kg
Dumping Height	38" / 0.97 m	56" / 1.42 m
Tires	12.5L x 15 - 6 ply	16.5L x 16.1 - 6 ply
Hitch	Multi-Position, Hydraulic Swing	Multi-Position, Hydraulic Swing
Hydraulic Requirements	12 - 15 gal/min. @ 1200 - 1500 PSI 45 - 57 L/min @ 83 - 103 bar	12 - 15 gal/min. @ 1200 - 1500 PSI 45 - 57 L/min @ 83 - 103 bar

Rock Windrowers	RW1200
Working width	11' 10" / 3.6 m
Height	32" / 81 cm
Weight	1,350 lbs. / 612.4 kg
Drive	Hydraulic
Transport Length	8' 11" / 2.7 m
Transport Width	12' 3" / 3.7 m
Tires	9.5L x 15
Reel	12" (30 cm) diameter

Because we are constantly striving to improve our products, we reserve the right to change the design, materials and specifications without notice.