

ATHENS

MODEL 62



The Model 62 is the ideal Tandem Disk Harrow for those who need to pass through lanes and narrow gates while still providing the performance of wider disks. The Model 62 is available in widths from 7'11" to 12'11" making it the perfect choice for smaller farms, plantations and ranches.



" WE PLOW THE EARTH "

www.athensplowcompany.com



MODEL 62 SPECIFICATIONS

WIDTH OF CUT	NUMBER OF DISCS	DISC SPACING		NUMBER OF BEARINGS	*APPROX. DBHP	APPROX. WEIGHT (lbs.)
		FRONT	REAR			
7'11"	20	9"	9"	8	40-50	1,646
8'2"	22	9"	7½"	8	45-55	1,768
	24	7½"	7½"			
9'4"	24	9"	9"	8	50-60	1,874
	26	9"	7½"			
	28	7½"	7½"			
10'6"	30	9"	7½"	8	55-65	2,088
	32	7½"	7½"			
10'9"	28	9"	9"	8	55-65	2,026
12'2"	32	9"	9"	12	65-75	2,336
12'11"	36	9"	7½"	12	70-80	2,526
	40	7½"	7½"			

*Approximate Draw Bar Horse Power is only a guide. Extremely hard, soft, hilly or boggy conditions will change these figures.

STANDARD EQUIPMENT

- Disc Blades, 20" or 22" Diameter
- Relube Quadriseal Ball Bearings
- Rigid Flangette Bearing Hangers
- 1½" Square Cold Rolled Axle
- Hydraulics Complete
- 15", 5 Lug Wheels with Quadriseal Hubs
- Spacing: 7½", 9" or 9" Front & 7½" Rear
- Angle of Cut: 13°, 17° or 21°
- Gang Wrench

OPTIONAL EQUIPMENT

- Scrapers
- Cover Discs
- Balk Buster



DISC BLADES

Available in 20 and 22 inch sizes. Athens Plow offers tailored solutions to meet your disking needs.

Smooth blades are best utilized in normal field conditions. They are more economical, wear longer, weigh more than cutout blades, and cut crop residue evenly.

Cutout blades are more aggressive and trap residue better than smooth blades.

The Quadriseal Wheel Hubs

are an exclusive ATHENS PLOW design for increased Bearing life and reduction of downtime. Our QUADRASEAL Wheel Hubs offer maximum protection from dirt and trash by combining a triple lip seal with a press fitted external trash flinger.

www.athensplowcompany.com

FEATURES

FRAME

The Main Frame is constructed of 4"x4" square tubing and 4" structural channel which is trussed braced and reinforced to resist twisting and bending.

GANGS

Rugged 3"x5" gang frame tubes provide rigid support for gang components. Gangs are factory assembled to 750 ft. lbs. and locked securely with slotted nuts.

AXLES


Axles are made from 1½" square cold rolled steel to insure straightness and to keep bearings and discs in alignment.

ANGLE OF CUT

Adjustments from 13° to 21° in 4° increments are made without tools by removing only one pin per gang.

VERSATILITY

The Tongue Clevis height can be adjusted to match the draw-bar height on the Tractor.



Athens Plow Co., Inc. guarantees each piece of equipment against defective materials and workmanship for a period of one year from the date of delivery to the purchaser unless otherwise specified. Athens Plow Co., Inc. reserves the right to make changes and/or improvements in design and construction of parts or machines without notice or obligation.