



TPX - 318 ROTARY CUTTER

18' Three Point Hitch Rigid/Flex Wing Mower

- Fixed knives and shrouding for optimum shredding performance and distribution when doing residue management in row crops like corn, cotton and sugar cane
- Adjustable wheel standards for shredding in virtually all row crop spacings
- Four position adjustable 3pt to keep cutter as close to the tractor as possible
- Heavy duty rubber coupler on drive line for protection in harsh conditions
- Fold up design for narrow transport width
- Greasable bushings everywhere for longer life
- Timed blades (without blade to blade contact) allow for a compact front to back length
- Large flotation skid steer tires (10.5" X 27") to minimize compaction
- Easy height adjustment on rear tires
- Double acting wings that can be locked off in rigid position for row crops or flex wing for ground contouring
- Only one hydraulic circuit needed to operate this unit
- Wide hinge gap to keep debris from falling on center deck when folding up wings



World Class *Built to Last*

schulte.ca

TPX-318 Specifications

SPECIFICATIONS

Splitter box
 Down boxes
 Tractor RPM
 1000
 Cutter shafts
 Center blade tip speed
 Wing blade tip speed
 Deck thickness
 Cut capacity
 Cut Width
 Side bands
 Blades
 3pt hitch
 Tires
 Transport width
 Machine height
 Cut height
 Blade over lap
 Safety deflectors
 Approximate weight
 Wing float (when in float position)
 Machine length
 Min HP
 Max HP

TPX-318

210hp (157kw)
 210hp (157kw)
 1000
 Cat 6 with clutch
 Cat 6 with rubber coupler
 16,308 (ft/min)
 16,308 (ft/min)
 10 ga (.34cm)
 3.5" (8.9cm)
 18.5' (5.64m)
 7ga x 14" (.46cm X 36cm)
 1/2" x 4" (1.3cm X 10.2cm)
 Cat 2 quick, cat 3, cat 3 quick, cat 4, cat 4 quick
 Skid steer - 10.5 (26.7cm) x 27" (68.6cm)
 116.5" (296cm) wing tip to wing tip
 8.75ft (2.67m)
 2" - 17" (5-43cm)
 3" (7.6cm)
 Single chains standard, rear and front belting option
 6,300lbs (2858kg)
 11 degrees down & 18 degrees up (lower cylinder mount), 0 degrees down & 20 degrees up (upper mount)
 12.7 ft (3.87 m)
 185 (136kw) (3pt lift capacity dependent)
 325 (239kw)

Front tractor weight kits may be required to ensure a minimum of 20% of total tractor weight is on front tires to maintain steering control and to prevent the front of the tractor from rearing up during operation.



Narrow transport position with wide hinge gap allows material to fall through instead of on to center deck




Fixed Knife and Safety Chains



Rear Castor Wheels



Deck Height Angle Adjustment



210hp (157kw) Splitter Box

OPTIONS - TPX-318

- 1-3/8 Z21 or 1-3/4 Z20 shaft
- Belting on front or back



Fixed Knife Baffling



Replaceable Skid Shoes



3pt Hitch Mount



210hp (157kw) Gear Box



Schulte Industries Ltd.
 PO Box 70, Englefeld, SK Canada S0K 1N0
 Ph (306) 287-3715 Fx (306) 287-3355
 Email info@schulte.ca Web www.schulte.ca



ISO 9001

Sold By:

Schulte is a registered trademark of Alamo Group Inc.

Schulte Industries Ltd. reserves the right to change the design and specifications of its products without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.

Printed in Canada

Prepared by NELSON GRAPHIC DESIGN

201907

