



A LANDOLL® Company

1205 Carry-All Specifications

Product Attributes	1205 Carry-All
Approximate Weight	7,450 lbs. (3,379 kg)
Working Width	12 ft. 0 in. (3.7 m)
Capacity - Heaped	5.5 yards (4.2 m ³)
Capacity - Struck	4.25 yards (3.2 m ³)
Transport Width	12 ft. 10 in. (3.9 m)
Shipping Width	8 ft. 6 in. (2.6 m)
Transport Height	6 ft. 6 in. (2.0 m)
Transport Clearance	18 in. (457 mm)
Overall Length	16 ft. 10 in. (5.1 m)
Cutting Edge	6 in. (152 mm) Hardened Steel
Hitch	Pintle Swivel Hitch
Tire Size	12.5L x 15 12 Ply
Spindle Size	2.75 in. (69.9 mm)
Wheel Hubs	8-Bolt, 6,500 lb. (2,948 kg)
Hydraulic Circuits Required	3
Lift/Tilt Cylinder	(1) 4.5 in. x 16 in. (114 x 406 mm)
Lift/Tilt Cylinder	(1) 4 in. x 16 in. (102 x 406 mm)
Gate Cylinder	(1) 4 in. x 16 in. (102 x 406 mm)
Safety Warning Lights & SMV Emblem	Standard
Safety Chain Kit	Standard