

SHREDDER



ROTAX® ENGINE	850 E-TEC (3700)	850 E-TEC Turbo R (3900)
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, turbocharged, 3-D R.A.V.E.™
Cylinders	2	2
Displacement	849 cc	849 cc
Bore	82 mm	82 mm
Stroke	80.4 mm	80.4 mm
Maximum engine speed	7,900 RPM	7,900 RPM
Carburation	Electronic Direct Injection with additional booster injectors	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Unleaded	Unleaded
Minimum octane	95 95	
Fuel tank	37 L / 9.8 gal	
Oil tank capacity (2-stroke)	3.4 L / 3.6 qt	

DIMENSIONS	
Overall vehicle length*	3,120 mm / 122.8 in. (3700) 3,250 mm / 124 in. (3900)
Overall vehicle width	1,120 mm / 44 in.
Overall vehicle height	1,280 mm / 50.4 in.
Ski stance	921 mm / 36 in.
Nominal track width	381 mm / 15 in.
Nominal track length	3,705 mm / 146 in. 3,912 mm / 154 in.
Track profile height	2.5 in. PowderMax (3700) 3 in. PowderMax Light (3900)

Bright White / Viper Red

POWERTRAIN

Gearbox	
Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, adjustable brake lever, plastic master cylinder with protector

CI	IIC	D	1S	n	N
31	J		10	\mathbf{U}	

COLOR

Front suspension	LFS
Front shock	KYB 36 CR Kashima
Rear suspension	PPS ² -DS+-3700 PPS ² -DS+-3900
Center shock	KYB 46 HLCR Kashima
Rear shock	KYB 46 HLCR Kashima

FEATURES

Frame	Radien²
Skis	Blade DS+
Seating	Shredder DS, 1-up
Handlebar	U-type aluminum with hooks, low grab handle
Riser block height	145 mm
Starter	Manual with SHOT

Reverse	RER
Heated throttle lever	Standard
Heated grips	Standard
Gauge	4.5 in. digital display 10.25 in. color display with BRP Connect (option)
USB power outlet	Yes, in front compartment
LinQ attachment	2 pairs



^{*}Overall vehicle length without snow flap.