



2023 CFORCE 600

Available colours



Inclusions

More than \$4,000 in included add-ons!

The most equipped vehicles on the market

Standard features and benefits

Hitch receiver \$100 value

5-year CFMOTO warranty \$2 000 value

3,000 Lbs Towing winch (complete assy) \$1000 value

Safety and convenience package

Including:

- Side mirrors
- Hand protectors
- USB plug
- 12v outlet
- LED headlight with integrated turn signals
- Horn

\$1000 value



5 Year limited warranty: 1 year complete with no milage restriction + 48 months balance powertrain only or 5,000 km

Starting at \$10 249*













Electric-power Engine management normal/work

charging port

Fuel injected

Cytech clutch system

Specifications

Motor

Type: Single-Cylinder, liquid-cooled, 4-valves, 4-strokes

Displacement: 580 cc

Bore & Stroke:

91 x 89,2 mm (3.58 x 3.5 in)

Compression: 10.7: 1

Engine management: Fuel injected engine

Cooling system: Liquid

Starting: Electric

Battery: 30 Amp

Size / weight

Length x width x height: 2 035 x 1 180 x 1 220 mm

(80 x 46.4 x 48 in)

Wheelbase: 1280 mm (50.4 in)

Ground clearance: 270 mm (10.6 in)

Minimum turning radius:

3625 mm (143 in)

Fuel tank capacity: 18 L (4.76 gal)

Net weight: 395 kg (870 lbs)

Rack capacity (Front/Rear):

Front 20 kg (44 lbs) Rear 40 kg (88 lbs)

Brakes

Four wheel hydraulic disc + rear wheel parking

Wheels

Front wheels:

Aluminum alloy (12 x 6 in)

Rear wheels:

Aluminum alloy (12 x 7.5 in)

Front tires: AT 25 X 8-12

Rear tires: AT 25 X 10-12

Transmission

CV-Tech IBC clutch system: variable transmission.

Gear box: L/H/N/R/P (parking lock shift system)

Power train: 2WD / 4WD, electric

locking differential

Suspension and direction

Front suspension: Double arm

independent

Front travel: 160 mm (6.3 in)

Rear suspension: Double A-arm

independant

Rear travel: 210 mm (8.2 in)

Steering: Electric power steering

Protection plan

EASY ptotection plan available













cfmoto.ca