MIXING BUSINESS WITH PLEASURE



2022 **UFORCE** 1000 EPS XL 6 UP

Available colours



Free More than \$5,000 in free add-ons!

The most equipped vehicles on the market

Standard features and benefits

Hitch receiver \$153 value

Roof \$459 value

Roof \$459 value

5-year CFMOTO warranty \$3 300 value

3,500 Lbs winch (complete assy) \$660 value

Safety and convenience package

Including:

- Lateral mirrors
- Retaining bars for passenger
- 12v outlet
- Flashers
- Horn

\$458 value



5 Year limited warranty: 1 year complete with no milage restriction + 48 months balance powertrain only or 5,000 km

Starting at \$18,999*









12V outlet



Specifications

Motor

Type: v-twin cylinder, 4-stroke, 8-valve

Displacement: 963 cc

Engine management: Fuel injected engine and digital ignition

Maximum toroue: 54 lbs/pi

Maximum power output: 71 hp

Cooling system: liquid

Starting: electric

Battery: 30 amp

Size / weight

Lenght x width x height: 3,770 x 1,615 x 1,850 mm (148 x 63,5 x 72,8 in)

Seat height: 585 mm

Wheelbase: 2,850 mm (112 in)

Minimum ground clearance:

280 mm (11 in)

Fuel tank capacity: 40 L (10.5 Gal) Curb weight: 945 kg (2083 lbs)

Towing capacity: 907 kg (2,000 lbs) Cargo box capacity:

453 kg (1000 lbs)

Brakes

Front: Dual hydraulic single piston galiper, 230 mm disc

Rear: Dual hydraulic single piston galiper, 230 mm disc

Wheels

Front wheels:

aluminium alloy (14 x 7 in)

Rear wheels:

aluminium alloy (14 x 8 in)

Front tires: at 27 x 9-14 (stag 8 ply rating)

Rear tires: at 27 x 11-14 (stag 8 ply rating)

Transmission

Cv-tech IBC clutch system: variable transmission

Gearbox: 1/h/n/r/p (parking lock shift system)

Power train: 2 wheels / 4 wheels drive, electric front locking differential

Suspension and direction

Front suspension: double a-arm independent suspension, hydraulic shock absorber, five adjustments spring preloads

Front travel: 230 mm (9.1 in)

Rear suspension: double a-arm independent suspension, external sway bar, hydraulic shock absorber, five adjustments spring preloads

Rear travel: 230 mm (9.1 in)

Steering: electric power steering



