

2025 SKANDIC® SE

Spring-only package with ultimate off-trail traction and flotation loaded with premium utility features.



SKANDIC SE
600R E-TEC SHOWN

SKANDIC SE
900 ACE SHOWN

// PACKAGE HIGHLIGHTS

- Two Rotax® engines available: 600R E-TEC® and 900 ACE™
- Available with four 20 in. or 24 in. track options
- Ultra large LinQ® utility cargo box with 135 L/35.7 US gal of storage
- Heated driver's visor power outlet
- 7.2 in. digital display
- Pilot™ 7.4 skis w/ liners
- KYB® 36 center and rear shocks
- Multi-LinQ plate with 125 lb/56.7 kg cargo capacity
- LTS telescopic front suspension
- SC®-5U articulating rear suspension with locking mechanism (no tool required)
- Removable passenger seat with grips
- Ultra-high windshield with side deflectors
- Air radiator with fan
- Standard electric start
- Deep snow running boards with large openings
- Easy Shift transmission (H-L-N) with RER™ electronic reverse (2-stroke)/electro-mechanical reverse (4 stroke)
- Pivoting mirrors
- pDrive™ clutch
- Low handlebar strap

ROTAX ENGINE

	600R E-TEC	900 ACE
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, four-stroke D.O.H.C., dry sump
Horsepower*	125	95
Cylinders - Displacement	2 - 599.4 cc	3 - 899 cc
Bore - Stroke (mm)	72.3 - 73	73 - 69.7
Fuel system	E-TEC direct injection	EFI
Fuel type - Octane	Premium unleaded - 91	Regular unleaded - 87
Fuel tank (L/US gal)	42/11.1	42/11.1
Oil tank capacity (L/qt)	3.4/3.6	3.3/3.5

POWERTRAIN

Drive clutch	pDrive with clickers/	pDrive
Driven clutch	QRS (20 in.) QRS Vent (24 in.)	QRS
Drive sprocket pitch (mm/in.)	73/2.86	

DRY WEIGHT

Dry weight 20 in track (lb)	651	675
Dry weight 24 in track (lb)	671	695

DIMENSIONS

Vehicle overall length (mm/in.)	3,222/126.9	
Vehicle overall width (mm/in.)	1,089/42.8	
Vehicle overall height (mm/in.)	1,513/59.6	
Ski stance (mm/in.)	889/35	
Available tracks (in.) (Length x width x profile)	Silent Cobra WT: 154 x 20 x 1.8 Silent Ice Cobra WT: 154 x 20 x 1.5	

Silent Cobra SWT: 154 x 24 x 1.5 opt.
Silent Ice Cobra SWT: 154 x 24 x 1.5 opt.

COLOR

Dusty Navy and Black	
Black	

SUSPENSION

Front suspension	LTS
Front shock	Motion Control
Front suspension travel (mm/in.)	150/5.9
Rear suspension	SC-5U
Center shock	KYB 36
Rear shock	KYB 36
Rear suspension travel (mm/in.)	239/9.4

FEATURES

Platform	REV® Gen4
Headlights	Halogen
Skis	Pilot 7.4 w/ liners
Seating	WideTrack 2-up
Handlebar	Standard with J-hooks/Grab handle
Riser block height (mm/in.)	145/5.7
Starter	Electric
Reverse	RER (600R E-TEC) Electro-mechanical (900 ACE)
Air radiator	Fan
Brake system	Brembo®
Heated throttle lever/grips	Standard (driver only)
Gauge type	7.2 in. digital
Windshield	Ultra-high with mirrors
Runner (in.) - Carbide (in.)	3/8 square - 4
Bumpers (front/rear)	Heavy-duty/Hitch receiver

// FEATURE HIGHLIGHTS



1 Multi-LinQ plate

Standard LinQ adaptable storage. Fits 16 and 20 in. wide LinQ accessories to maximize accessory options. Up to 125 lb (56.7 kg) of cargo capacity.



2 Ultra large LinQ utility cargo box

135 L/35.7 US gal of lockable, weather-resistant storage capacity. Incorporated hatchet and saw holder, plus attachment points for bungees and two 16 in. LinQ positions on top for expandable accessory use.



3 LTS front suspension

Industry-exclusive telescopic front suspension enables a large, flat belly pan for exceptional deep snow flotation.



SKANDIC SE
900 ACE SHOWN



4 Ski liners

Added flotation for extreme capability when your day takes you into the deep stuff.



5 20 in. and 24 in. wide tracks available

A wide range of options built to offer superb flotation and meet any towing needs.



6 SC-5U articulating rear suspension

The articulated rail maximizes deep snow traction in reverse, and its toolless locking mechanism is ideal for towing.

ski-doo

