

	550A	570A	582A	750A	770A	782A	4100A HP	4120A HP
<b>Performance</b>								
Field Width	50'	70'	82'	50'	70'	82'	100'	120'
Minimum Horsepower	150	200	300	285	400	475	500	550
Weight (lbs)	10,300	12,900	14,200	11,500	14,200	16,300	43,550	46,550
<b>Wing Control</b>								
Solid Pull Draw Bar	4" x 4" x 3/16"	4" x 4" x 3/16"	4" x 4" x 3/16"	4" x 4" x 3/16"	4" x 4" x 3/16"	4" x 4" x 3/16"	5" x 5" x 3/8"	5" x 5" x 3/8"
Booms	8" x 8" x 1/4"	8" x 8" x 1/4"	8" x 8" x 3/8"	8" x 8" x 1/4"	8" x 8" x 1/4"	8" x 8" x 3/8"	12" x 16" x 3/8"	12" x 16" x 3/8"
Lift Cylinders	4" x 30" Cylinder - 2" Rod	4" x 30" Cylinder - 2" Rod	4" x 30" Cylinder - 2" Rod	4" x 30" Cylinder - 2" Rod	4" x 30" Cylinder - 2" Rod	4" x 30" Cylinder - 2" Rod	4" x 24" Cylinder - 2" Rod	4" x 24" Cylinder - 2" Rod
Wing Latch Cylinders	4" Cylinder - 2" Rod	4" Cylinder - 2" Rod	4" Cylinder - 2" Rod	4" Cylinder - 2" Rod	4" Cylinder - 2" Rod	4" Cylinder - 2" Rod	4" Cylinder - 2" Rod	4" Cylinder - 2" Rod
U-Joint Pin Diameter	2"	2"	2"	2"	2"	2"	2.5"	2.5"
<b>Transport</b>								
Width	14'	14'	14'	14'	14'	14'	18'	18'
Length	42'	52'	58'	42'	52'	58'	75' 6"	85' 6"
Height	11'	11'	11'	12'	12'	12'	12'	12'
<b>Harrow Sections</b>								
Tine Adjust	Manual or Hydraulic	Manual or Hydraulic	Manual or Hydraulic	Manual or Hydraulic	Manual or Hydraulic	Manual or Hydraulic	Manual	Manual
Tines Sizes	1/2" x 26" or 5/8" x 28"	1/2" x 26" or 5/8" x 28"	1/2" x 26" or 5/8" x 28"	1/2" x 26"	1/2" x 26"	1/2" x 26"	5/8" x 30"	5/8" x 30"
Tine Tips	Standard or Carbide	Standard or Carbide	Standard or Carbide	Standard or Carbide	Standard or Carbide	Standard or Carbide	Ultra-Wear-Resistant Carbide Tips	
Tine Spacing	18" Centers	18" Centers	18" Centers	14" Centers	14" Centers	14" Centers	24" Centers	24" Centers
Bars Per Section	5	5	5	7	7	7	4	4
Section Width	5 x 10'	7 x 10'	7 x 10' + 2 x 6'	5 x 10'	7 x 10'	7 x 10' + 2 x 6'	10 x 10'	12 x 10'
Tine Angle	5 - 65 degrees	5 - 65 degrees	5 - 65 degrees	5-65 degrees	5 - 65 degrees	5 - 65 degrees	5 - 50 degrees	5 - 50 degrees
<b>Tires</b>								
Center Tires	500/45R22.5 (16 ply) Flotation Tires or 16.5L x 16.1 (14 ply) Rib Implement Tires						550/45-22.5 High Flotation Tires	
Wing Field Tires	31 x 13.50 x 15 (10 ply) High Flotation Boom Field Tires						550/45-22.5 High Flotation Tires	
Wing Transport Tires	235/85R16 - Road Tire						-	-
<b>Hitch</b>								
Standard Hitch	Cat 4	Cat 4	Cat 4	Cat 4	Cat 4	Cat 4	Cat 5	Cat 5
Optional Crossover Hitch	Yes	Yes	Yes	Yes	Yes	Yes	-	-
Optional Ball-Socket Hitch	Yes, Cat 4 or Cat 5	Yes, Cat 4 or Cat 5	Yes, Cat 4 or Cat 5	Yes, Cat 4 or Cat 5	Yes, Cat 4 or Cat 5	Yes, Cat 4 or Cat 5	-	-

**For more information**

Call us at 1-866-4-BRANDT  
 Email us at agriculture@brandt.ca  
 Or visit us at www.brandt.ca

**Brandt Agricultural Products**

PO Box 317, 13th Avenue & Pinkie Road  
 Regina, SK, Canada  
 S4P 3A1