

A guarantee of quality
for nearly 40 years

FLEX-MIX

MANURE PUMPS



teamco.ca

TEAMCO™



**RECOMMENDED TRACTOR
140 TO 180HP PTO (540RPM)**

Available in length of 12', 14' and 16'



SHREDDING SCREW WITH IMPELLER



ARTICULATED IMPELLER

SHREDDING SCREW

About 75% of the power is required by the impeller. The tractor's hp is transmitted directly to the impeller without going through gears. Requiring less power, the shredding screw is driven by the gear box. With this system, manure is shredded and sucked up in record time.

IMPELLER

The flex-mix is a manure pump that empties your pit to its lowest level due to its articulated 540 RPM impeller. Equipped with cutters, the impeller completes the shredding screw's work.

SYNCHRONIZED ARTICULATION

This Teamco designed system uses only one cylinder to perfectly synchronize movement. The operator does not need to calibrate the driveshafts' angles. This system eliminates vibration caused by wrong driveshaft angles.

REMOTE CONTROL

The remote controls the different pump functions, either from beside the pump or from the spreading tractor.

ROTATING STIRRING NOZZLE

The 4 inches stirring nozzle is the most powerful on the market. It's also the most manoeuvrable with its 245° horizontal and 150° vertical swings.

HYDRAULIC LOADING ARM 8"

This feature allows a pumping rate of up to 2600 gallons per minute to fill a spreader located left or right of the pump.



SYNCHRONIZED ARTICULATION



REMOTE CONTROL



ROTATING STIRRING NOZZLE



HYDRAULIC LOADING ARM 8"

Since 1978, Teamco equipments have earned a reputation that outclasses all competition with its long lasting and anti-corrosion qualities.

The success of Teamco comes in part from the sandblasting preparation, the select epoxy primer, urethane paint and the rigorous application procedures.

TEAMCO™

**Machinerie agricole
Bois-Francis Inc.**
2, rue du Parc
Warwick (Québec) Canada JOA 1M0

Tel.: 1 888 358-6808
Fax: 819 358-2015
venteag@teamco.ca
teamco.ca

