



BAUMAN
MANUFACTURING

Tel. (519) 669-4333 Fax 1-800-572-6796
sales@baumanmfg.com

QUICK REFERENCE for Cross & Bearing Kits



A Snap Ring located in the bushing (Internal)

B Snap Ring located in the yoke (External)

NORTH AMERICAN

WEASLER (R) STOCK NO.	WEASLER (E) STOCK NO.	SERIES	(R) KIT RATED H/P @ 540 RPM	(E) KIT RATED H/P @ 540 RPM	(R) KIT RATED H/P @1000 RPM	(E) KIT RATED H/P @1000 RPM	BEARING DIAMETER	CAP TO CAP OVERALL LENGTH	SNAP RING TYPE
200-0100	N/A	Rockwell 1FR	N/A	N/A	N/A	N/A	7/8"	2 15/16"	B
200-0300	N/A	Rockwell 3DR	N/A	N/A	N/A	N/A	1"	3 15/16"	B
200-0600	201-0600	6	14	19	21	29	31/32"	2 5/16"	A
200-0675	N/A	675	15	N/A	24	N/A	15/16"	2 5/16"	A
200-0700	N/A	W	N/A	N/A	N/A	N/A	9/16"	1 1/2"	Pin & Block
200-1000	N/A	1000	15	N/A	24	N/A	15/16"	2 9/32"	A
200-1200	201-1200	12	19	26	29	40	1 1/16"	2 1/2"	A
200-1400	201-1400	14	28	38	44	58	1 1/8"	2 5/8"	B
200-1875	N/A	1800	30	N/A	48	N/A	1"	3 7/16"	A
200-2600	N/A	2600	100	N/A	144	N/A	1 3/8"	4 3/16"	B
200-3500	201-3500	35	51	70	79	108	1 1/4"	3 7/32"	B
200-4400	201-4400	44	77	103	119	158	1 5/16"	4"	A
200-5500	201-5500	55	106	137	164	211	1 17/32"	4 5/16"	B

ITALIAN SERIES

WEASLER (R) STOCK NO.	WEASLER (E) STOCK NO.	SERIES	(R) KIT RATED H/P @ 540 RPM	(E) KIT RATED H/P @ 540 RPM	(R) KIT RATED H/P @1000 RPM	(E) KIT RATED H/P @1000 RPM	BEARING DIAMETER	CAP TO CAP OVERALL LENGTH	SNAP RING TYPE
200-6154	201-6154	1	15	19	23	29	22.0 mm	54.0 mm	B
200-8261	201-8261	2	21	25	33	38	23.8 mm	61.2 mm	B
200-8370	201-8370	3	29	38	44	58	27.0 mm	70.0 mm	B
200-8474	201-8474	4	36	45	56	70	27.0 mm	74.6 mm	B
200-6580	201-6580	5	52	65	81	100	30.2 mm	79.6 mm	B
200-8692	201-8692	6	64	79	99	122	30.2 mm	92.0 mm	B
200-6794	201-6794	7N	79	94	122	145	34.9 mm	94.0 mm	B
200-6806	201-6806	8	100	120	154	185	34.9 mm	106.5 mm	B
200-6908	201-6908	9	120	151	185	232	41.0 mm	108.0 mm	B

GERMAN SERIES

WEASLER (R) STOCK NO.	WEASLER (E) STOCK NO.	SERIES	(R) KIT RATED H/P @ 540 RPM	(E) KIT RATED H/P @ 540 RPM	(R) KIT RATED H/P @1000 RPM	(E) KIT RATED H/P @1000 RPM	BEARING DIAMETER	CAP TO CAP OVERALL LENGTH	SNAP RING TYPE
200-7155	201-7155	2100	16	19	23	29	22.0 mm	54.8 mm	B
200-8261	201-8261	2200	21	25	33	38	23.8 mm	61.2 mm	B
200-8370	201-8370	I	30	38	44	58	27.0 mm	70.0 mm	B
200-8474	201-8474	2300	37	45	56	70	27.0 mm	74.6 mm	B
200-8692	201-8692	220	64	79	99	122	30.2 mm	92.0 mm	B
200-7676	201-7676	2400	53	66	80	102	32.0 mm	76.0 mm	B
200-7989	201-7989	2500	80	94	124	144	36.0 mm	88.8 mm	B
200-7004	201-7004	2600	113	149	175	230	42.0 mm	104.0 mm	B