




**Artificial  
Lift  
XWerx Ltd.**

**640-365-168**



A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	BACK WIDTH	FRONT WIDTH	OVERALL WIDTH
120.00	202.50	262.00	120.00	144.00	110.00	48.00	112.00	62.00	168.00	17.50	160.00	241.50	295.50	54.00	360.00	456.25	33.50	72.00	105.50

#### EFFECTIVE COUNTERBALANCE DATA

Weight Combination	Counter Balance Effect
Crank Only	6419
2 #15	9841
2 #16	11114
2 #17	13823
2 #15 + #16	14536
4 #16	15810
2 #15 + #17	17245
2 #18	17147
2 #16 + #17	18518
2 #15 + #18	20569
4 #17	21227
2 #16 + #18	21842
2 #17 + #18	24551
4 #18	27875

#### GENERAL ENGINEERING DATA

Peak Torque Rating, API	640,000 in-lbs
Polish Rod Capacity	36,500 lbs
Stroke Lengths	168", 144", 122"
Walking Beam Size	33"@221 lbs
Reducer Model	T640
Reducer Ratio	29.32
Input Shaft Size	4.000
Max. Sheave Diameter	50.4"-6C
Belts for Std High Mount	C240
Oil Capacity	450L
Structural Unbalance	1278 lbs
Gear Box Weight	11440 lbs
Total Weight	* 44266 lbs

\* NOT INCLUDING COUNTER WEIGHT

Counter Weights	Weight	Crank Arm	Weight
#15	1494 lbs	R48	3800 lbs
#16	2100 lbs		
#17	3500 lbs		
#18	5300 lbs		

**GET PUMPED UP AT "WWW.ALXJACKS.COM"**



**640-365-168**

### STANDARD EQUIPMENT

- \* High Mount Assembly
- \* Bendix Style Brake
- \* Mesh Crank Arm Guards
- \* Bridle Assembly
- \* Dual Rail Tie Down Bars
- \* Adjustable Motor Rails
- \* 2 Ladders With Safety Cages
- \* Cable Fall Restraint
- \* Wrist Pin Wrench
- \* Gear Oil Fill
- \* T Bolts
- \* Painted Black & Safety Yellow

### OPTIONAL EQUIPMENT

- \* Counter Balance Weights
- \* Electric Motors
- \* Triple Rated Electric Motors
- \* Low Oil Level Switch
- \* Full Guard With Mesh
- \* Fiberglass Full Guard
- \* Concrete Bases
- \* Colour Options
- \* Low Mount Brake Cables
- \* Low Mount Engine Rails
- \* Drive Sheave & Belts
- \* Vibration Switches
- \* Central Lubrication
- \* Full Guard Enclosed
- \* Partial Belt Guard
- \* Pressure Treated Stripping
- \* Low Mount Brake Mount
- \* Speciality Lube Oils

### CONSTRUCTION FEATURES

- \* Manufactured To API 11E Specifications
- \* ISO/Q1 Approved Fabrication Plant
- \* CWB Welded To W48
- \* Mono Gear Box Mounting Plate
- \* Three Leg Sampson Post - Removable Third Leg
- \* Saddle Bearing - Double 6" x 11" Railroad Style
- \* Split Case Gear Boxes
- \* Replaceable Wrist Pin Sleeves
- \* Hangar Style Rear Equalizer
- \* Pitman Arm Utilize Brass Bearings For Quiet Operation
- \* Common Off The Shelf Bearings and Seals

## ALX PUMPING UNITS

#### Please Call For Quote:

ALX Sales Canada: 1-866-ALX-JACK (259-5225)

#### Address:

**ALX Plant**  
521 6th Street  
Estevan, SK  
S4A-1A4

**Corporate Office**  
P.O. Box 695  
Estevan, SK  
S4A-2A6

Date: January 15, 2022

**GET PUMPED UP AT [WWW.ALXJACKS.COM](http://WWW.ALXJACKS.COM)**