



LAZER Z[®] X-SERIES

UNMATCHED PERFORMANCE. LEGENDARY DURABILITY.

FEATURES

UltraCut™ Deck Technology

Side Discharge: 60 | 72

Commercial-Grade Engines

Kohler®, Kawasaki® or Vanguard®

Unibody Frame

Fully welded tubular frame design places major components like the engine, hydro-drive and fuel tank lower for better mass centralization

Hydro-Drive System

Eliminated hoses and added tougher bearings, an improved cooling system and increased oil capacity.



MAINTENANCE MADE EASY

Lazer Z mowers are engineered to have fewer things to inspect, lubricate, adjust and repair. With only four grease points and longer service intervals, thanks to the Oil Guard™ System (select models), your Lazer Z is always ready for the job.



THE SIGNATURE CUT

We've optimized the blade-tip speed of the UltraCut decks to perfect the distance and uniformity of clipping discharge. All the components in our deck work together to deliver the signature Exmark look, cut after cut. Job after job.

TOP ACCESSORIES

- Air Ride Suspension Kit
- LED Light Kit
- Micro-Mulch System
- Operator Controlled Discharge
- Sun Shade
- Tractus Tire
- Trash Container
- Turf Striping Kit
- UltraVac Collection Systems

Accessories may not fit each mower model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

The commercial mowers more landscape pros trust.

exmark.com

LAZER Z X-SERIES

MODEL	ENGINE	SIZE	DECK	WEIGHT	DIMENSIONS (W X H X L)
LZX801GKA606A1	FX801V Kawasaki	60"	UltraCut Series 6	1209 lbs.	72.8" x 70.5" x 83.1"
LZX801CKA606C1	FX801V Kawasaki	60"	UltraCut Series 6	1302 lbs.	72.8" x 70.5" x 83.1"
LZX921GKA606A1	FX921V Kawasaki	60"	UltraCut Series 6	1250 lbs.	72.8" x 70.5" x 83.1"
LZX980EKC606W0	ECV980 Kohler EFI RED Equipped	60"	UltraCut Series 6	1246 lbs.	72.8" x 70.5" x 83.1"
LZX993EBV606X1	993 Vanguard EFI w/ Oil Guard System	60"	UltraCut Series 6	1372 lbs.	72.8" x 70.5" x 83.1"
LZX921GKA726A1	FX921V Kawasaki	72"	UltraCut Series 6	1294 lbs.	84.9" x 70.5" x 86.1"
LZX980EKC726W0	ECV980 Kohler EFI RED Equipped	72"	UltraCut Series 6	1196 lbs.	84.9" x 70.5" x 86.1"
LZX993EBV726X1	993 Vanguard EFI w/ Oil Guard System	72"	UltraCut Series 6	1412 lbs.	84.9" x 70.5" x 86.1"



Side Discharge
with Suspension Platform



Side Discharge with **RED**



Side Discharge with
Oil Guard System

POWER COMPONENTS

Engine – ECV980 Kohler Command EFI; FX801V and FX921V Kawasaki; 993 Vanguard BIG BLOCK EFI with Oil Guard System. All engines governed to 3,750 rpm except RED units are 3,650 rpm.

Air Filter – Heavy-duty canister air filtration system.

Drive System – Two Exmark® exclusive Parker unitized pump and wheel motor systems with no hoses, integrated cooling fans, 1.7-quart integrated reservoir, spin-on filter and heavy-duty components. 16cc pumps and 17.1 cubic inch motors with shock valves.

Hydro Fluid – Exmark Premium Hydro Oil.

Speed – Infinitely variable speed selection from 0–11.5 mph (18.5 kmph) forward, 0–7.0 mph (11.3 kmph) reverse.

PTO Engagement – MagStop Electromagnetic 250-ft-lbs clutch with spot brake except FX801V has 200-ft-lbs.

Fuel Capacity – High-capacity, 12-gallon (45.4-L), single fuel tank with single fill location.

Drive-Wheel Release – Allows unit movement without engine running.

Safety Package – Operator Presence Controls (OPC) and drive system interlock, with safety interlock system indicators.

Rollover Protection System (ROPS) – 2-post foldable ROPS standard with seat belt and latch.

Quick Deck Lift – Standard; foot-controlled deck lift changes cutting height and lifts the deck to maneuver around obstacles, or place in transport position.

DECK

Style – Full-floating UltraCut Series 6 featuring a heavy-duty spindle. Side-discharge standard with the option to bag or mulch.

Deck Construction – 10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 7-gauge formed and welded spindle mounting reinforcements for improved strength and reduced weight. 4-point suspension, full floating deck. 72" unit has 6 adjustable, cone-shaped, anti-scalp rollers. 60" unit has 4 adjustable, cone-shaped, anti-scalp rollers.

Widths Available – 60" (152 cm) and 72" (183 cm).

Cutting Height – 1.0" (2.5 cm) to 5.5" (11.8 cm) in 0.25" (0.64 cm) increments adjustable from operator's seat.

Blade Spindles – No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 1.75"-diameter splined blade driver and 30mm diameter spindle shaft.

Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Tractor Frame – Unibody, welded, heavy-duty 1.5" x 3" tubular steel.

Steering and Motion Control – Hydraulically dampened twin levers, adjust fore and aft, also adjustable to 2-height positions. Adjustable dampers (3-positions) to customize drive responsiveness.

Casters – .50" thick caster yoke arm.

Front Caster Tires – 13 x 6.5–6 smooth tread, semi-pneumatic tires.

Drive Tires – 24 x 12.0–12, 4-ply Turf Master.

Turning Radius – True zero-turn.

Parking Brake – Lever-actuated disc brake.

Seat Comfort – Deluxe, bolstered suspension seat with Elastomeric Vibration Control material. Mounted on innovative Seat Isolation System that provides operator isolation in all three planes of motion as well as fore-aft slide and seat flip-up. C1 models include a suspension platform. The suspended operator platform maximizes productivity through increased operator comfort.

Onboard Intelligence – W0 models are equipped with Next-Generation RED technology.

Electrical – All have 12-volt battery. 15-amp alternator on Kawasaki units. 20-amp on Kohler units.

Standard Features – Engine hour meter and cup holder.

ACCESSORIES & OPTIONS

3-Bushel Bagger, 12-Volt Power Adapter, Air Ride Anti-Scalp Kit, Suspension Seat, Equipment Cover, Extended Drive Lever, Floor Mat, Hitch, Hydro Maintenance Kit, Jack and Receiver, LED Light Kit, Micro-Mulch System, Operator Controlled Discharge, Pedal Adapter Kit, Power Deck Lift, Sun Shade, Tractus Tire, Trash Container, Turf Striping Kit and UltraVac Collection Systems.

Accessories may not fit each model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

WARRANTY

Limited Warranty: 5-Year or 1,500 Hours (with No Hour Limit First 2 Years), 3 Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • exmark.com

¹ Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x width of cut = 99 = acres per hour | 80% efficiency: MPH x width of cut = 124 = acres per hour.

² For complete details, visit exmark.com or your local dealer.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Lazer Z® are registered trademarks of Exmark Mfg. Co., Inc. ©2022 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2022. Rev 1.